



ACS02E-18-9SB(003) Information

Heisener.com

Part Number ACS02E-18-9SB(003)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 7POS BOX MNT W/SCKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACS02E-18-9SB(003) Specifications

Manufacturer Part Number ACS02E-18-9SB(003) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series AC-B, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 18-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC-B, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	ACS02E-18-9SB(003)
Package-SeriesAC-B, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - AC-B, MIL-5015 Derivative Connector Type Receptacle, Female Sockets Number of Positions 7 Shell Size - Insert 18-9 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating	Category	Connectors, Interconnects
SeriesAC-B, MIL-5015 DerivativeConnector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions7Shell Size - Insert18-9Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Series	AC-B, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Number of Positions	7
Mounting TypePanel Mount, FlangeTerminationSolderFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	18-9
Termination Solder Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated 5 Silver - - - - - - - - - - - - -	Orientation	N (Normal)
Contact Finish Features - Voltage - Rated Current Rating Silver - 200VAC, 250VDC -	Ingress Protection	Environment Resistant
Features - Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
•	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

ACS02E-18-9SB(003) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACS02E-18-9SB(003) Payment Methods



















ACS02E-18-9SB(003) Shipping Methods













If you have any question about ACS02E-18-9SB(003), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com