

ACS06A-20-15S(025) Information

Heisener.com

ACS06A-20-15S(025) Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors**

Description CONN PLUG 7POS INLINE SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACS06A-20-15S(025) Specifications

Manufacturer Part Number ACS06A-20-15S(025) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating Page of the process		
Category Connectors, Interconnects Circular Connectors Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating - Connectors AC, MIL-5015 Derivative Plug, Females AC, MIL-5015 Derivative Plug, Female Sockets AC, MIL-5015 Derivative Plug, Females AC, MIL-5015 Derivative Plug, Female Sockets Plug,	Manufacturer Part Number	ACS06A-20-15S(025)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 7 Shell Size - Insert 20-15 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert20-15Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 20-15 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Series	AC, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	20-15
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating Aluminum, Black Zinc Cobalt Plated Silver Mounting Hardware, Strain Relief	Orientation	N (Normal)
Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Ingress Protection	-
Features Mounting Hardware, Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	500VAC, 700VDC
Donost owners?	Current Rating	-
Report errors?		Report errors?

ACS06A-20-15S(025) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACS06A-20-15S(025) Payment Methods



















ACS06A-20-15S(025) Shipping Methods













If you have any question about ACS06A-20-15S(025), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com