



## ACS06E-14S-6P(553) Information

Heisener.com

Part Number ACS06E-14S-6P(553)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ACS06E-14S-6P(553) Specifications

Manufacturer Part NumberACS06E-14S-6P(553)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedConact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDC		
Category Connectors, Interconnects Circular Connectors  Package - Series AC, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated  Convertified  Connectors, Interconnects Circular Connectors  AC, MIL-5015 Derivative AC, MIL-5015 Derivative Feetures AC, MIL-5015 Derivative Feetures AC, MIL-5015 Derivative Feetures AL, MIL-5015 Derivative Feetures AC, MIL-5015 Derivative AC, MIL-	Manufacturer Part Number	ACS06E-14S-6P(553)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDC	Manufacturer	Amphenol Industrial Operations
Package - Series AC, MIL-5015 Derivative Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative  Connector Type Plug, Male Pins  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC		Circular Connectors
Connector Type Plug, Male Pins  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC	Package	-
Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated  6  6  Contact Finish Features Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Mounting Hardware, Strain Relief	Series	AC, MIL-5015 Derivative
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  14S-6	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDC	Shell Size - Insert	14S-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC	Orientation	N (Normal)
Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC	Ingress Protection	Environment Resistant
Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 200VAC, 250VDC	Contact Finish	Silver
	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	200VAC, 250VDC
Current Rating -	Current Rating	-
Report errors?		Report errors?

## ACS06E-14S-6P(553) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ACS06E-14S-6P(553) Payment Methods





















## ACS06E-14S-6P(553) Shipping Methods













If you have any question about ACS06E-14S-6P(553), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com