



## ACS06E-14S-6S(027) Information

Heisener.com

ACS06E-14S-6S(027) Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ACS06E-14S-6S(027) Specifications

Manufacturer Part Number     ACS06E-14S-6S(027)       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     AC, MIL-5015 Derivative       Connector Type     Plug, Female Sockets       Number of Positions     6       Shell Size - Insert     14S-6       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Environment Resistant       Shell Material, Finish     Aluminum, Black Zine Cobalt Plated       Contact Finish     Silver       Features     Mounting Hardware, Strain Relief       Voltage - Rated     200VAC, 250VDC       Current Rating     -       Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating - Connectors AC, MIL-5015 Derivative Plug, Female AC, MIL-5015 Derivative Plug, Female AC, MIL-5015 Derivative Plug, Female Sockets AC,	Manufacturer Part Number	ACS06E-14S-6S(027)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Characteristic - Solder Cup - Solder Cup Fastening Type Threaded - Corientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating - Solder Solde	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative  Connector Type Plug, Female Sockets  Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating -	Series	AC, MIL-5015 Derivative
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  Coverent Rating  -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating	Number of Positions	6
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Size - Insert	14S-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Mounting Hardware, Strain Relief  Voltage - Rated  Current Rating	Orientation	N (Normal)
Contact Finish  Features  Mounting Hardware, Strain Relief  Voltage - Rated  200VAC, 250VDC  Current Rating  -	Ingress Protection	Environment Resistant
Features Mounting Hardware, Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 200VAC, 250VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

## ACS06E-14S-6S(027) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ACS06E-14S-6S(027) Payment Methods



















## ACS06E-14S-6S(027) Shipping Methods













If you have any question about ACS06E-14S-6S(027), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com