



ACS06E-14S-6S(553) Information

Heisener.com

Part Number ACS06E-14S-6S(553)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 6POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ACS06E-14S-6S(553) Specifications

Manufacturer Part Number ACS06E-148-6S(553) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -		
Category Connectors, Interconnects Circular Connectors Package - Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating -	Manufacturer Part Number	ACS06E-14S-6S(553)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating	Category	Connectors, Interconnects
Series AC, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesMounting Hardware, Strain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating -	Series	AC, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating	Number of Positions	6
Mounting Type Free Hanging (In-Line) Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size - Insert	14S-6
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Mounting Hardware, Strain Relief Voltage - Rated Current Rating Aluminum, Black Zinc Cobalt Plated Silver Mounting Hardware, Strain Relief	Orientation	N (Normal)
Contact Finish Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Ingress Protection	Environment Resistant
Features Mounting Hardware, Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Mounting Hardware, Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

ACS06E-14S-6S(553) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ACS06E-14S-6S(553) Payment Methods



















ACS06E-14S-6S(553) Shipping Methods













If you have any question about ACS06E-14S-6S(553), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com