



Heisener.com

### ACS06F-28-16SB(025) Information

Part Number ACS06F-28-16SB(025)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

**Description** CONN PLUG 20POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ACS06F-28-16SB(025) Specifications

Manufacturer Part Number       ACS06F-28-16SB(025)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       AC-B, MIL-5015 Derivative         Connector Type       Plug, Female Sockets         Number of Positions       20         Shell Size - Insert       28-16         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Black Zinc Cobalt Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC-B, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	ACS06F-28-16SB(025)
Package-SeriesAC-B, MIL-5015 DerivativeConnector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - Series AC-B, MIL-5015 Derivative Connector Type Plug, Female Sockets Number of Positions 20 Shell Size - Insert 28-16 Shell Size, MIL - Changing (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating - Solder Cup Strain Relief Contact Finish Silver Features Strain Relief	Category	Connectors, Interconnects
Series AC-B, MIL-5015 Derivative  Connector Type Plug, Female Sockets  Number of Positions 20  Shell Size - Insert 28-16  Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions20Shell Size - Insert28-16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Cobalt PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	AC-B, MIL-5015 Derivative
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating	Number of Positions	20
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Black Zinc Cobalt Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Size - Insert	28-16
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Cobalt Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Black Zinc Cobalt Plated  Silver  Strain Relief	Orientation	N (Normal)
Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  Silver  Strain Relief	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

### ACS06F-28-16SB(025) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ACS06F-28-16SB(025) Payment Methods



















# ACS06F-28-16SB(025) Shipping Methods













If you have any question about ACS06F-28-16SB(025), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com