



### ACS08E-16S-1P(472) Information

Heisener.com

Part Number ACS08E-16S-1P(472)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 7POS INLINE PIN RA

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ACS08E-16S-1P(472) Specifications

Manufacturer Part Number       ACS08E-16S-1P(472)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       AC, MIL-5015 Derivative         Connector Type       Plug, Male Pins         Number of Positions       7         Shell Size - Insert       16S-1         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Solder         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Black Zinc Alloy Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       500VAC, 700VDC         Current Rating       -         Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert16S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	ACS08E-16S-1P(472)
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert16S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert16S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesAC, MIL-5015 DerivativeConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert16S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert16S-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions  Shell Size - Insert  16S-1  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Alloy Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Series	AC, MIL-5015 Derivative
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line), Right Angle  Termination  Solder  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Black Zinc Alloy Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Solder  Fastening Type Threaded Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Alloy Plated  Contact Finish Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating	Number of Positions	7
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Black Zinc Alloy PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	16S-1
Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Alloy Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Alloy Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Alloy Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Black Zinc Alloy Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Black Zinc Alloy Plated  Silver  Strain Relief	Orientation	N (Normal)
Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  Silver  Strain Relief	Ingress Protection	Environment Resistant
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating -	Shell Material, Finish	Aluminum, Black Zinc Alloy Plated
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

### ACS08E-16S-1P(472) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ACS08E-16S-1P(472) Payment Methods



















### ACS08E-16S-1P(472) Shipping Methods













If you have any question about ACS08E-16S-1P(472), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com