



AD10048P3L-001 Information



For Reference Only

Part Number AD10048P3L-001

Manufacturer Artesyn Embedded Technologies

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 48V 100W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD10048P3L-001 Specifications

Manufacturer Part Number AD10048P3L-001 Manufacturer Artesyn Embedded Technologies Category Power Supplies - External/Internal (Off-Board) Reckage - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Manufacturer Part Number	AD10048P3L-001
Package-Series-Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output48VCurrent - Output (Max)2.08APower (Watts)100WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Manufacturer	Artesyn Embedded Technologies
Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output48VCurrent - Output (Max)2.08APower (Watts)100WNo Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 45°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 37.2mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 45° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Series	-
Input TypeCord (Sold Separately)Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 6.14° L $x 2.56^{\circ}$ W $x 1.47^{\circ}$ H (156.0mm $x 65.0\text{mm } x 37.2\text{mm}$)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 48 V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $6.14^{\circ}\text{ L} \times 2.56^{\circ}\text{ W} \times 1.47^{\circ}\text{ H} (156.0\text{mm} \times 37.2\text{mm})$	Form	Desktop (Class I)
Voltage - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) 100W No Load Power Consumption	Voltage - Output	48V
No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 45°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Current - Output (Max)	2.08A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $6.14^{\circ}\text{L} \times 2.56^{\circ}\text{W} \times 1.47^{\circ}\text{H} (156.0 \text{mm} \times 37.2 \text{mm})$	Power (Watts)	100W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 45° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14° L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	No Load Power Consumption	-
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $6.14^{\circ}\text{L} \times 2.56^{\circ}\text{W} \times 1.47^{\circ}\text{H} (156.0 \text{mm} \times 37.2 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 45^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $6.14^{\circ}\text{L} \times 2.56^{\circ}\text{W} \times 1.47^{\circ}\text{H} (156.0\text{mm} \times 37.2\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Efficiency	Level V
Size / Dimension 6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)	Operating Temperature	0°C ~ 45°C
· · ·	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	6.14" L x 2.56" W x 1.47" H (156.0mm x 65.0mm x 37.2mm)
		Report errors?

AD10048P3L-001 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD10048P3L-001 Payment Methods


































If you have any question about AD10048P3L-001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com