



AD7248JNZ Information



For Reference Only

Part Number AD7248JNZ

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Data Acquisition - Digital to Analog Converters

(DAC)

Description IC DAC 12BIT W/REF 20-DIP **Package** 20-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD7248JNZ Specifications

Manufacturer Part Number AD7248JNZ Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 20-DIP (0.300", 7.62mm) Series DACPORT? Number of Bits 12 Number of D/A Converters 1 Settling Time 5μs, 10μs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±14.25 V ~ 15.75 V Voltage - Supply, Digital 14.25 V ~ 15.75 V Voltage - Supply, Digital 14.25 V ~ 15.75 V Voltage - Supply Digital 14.25 V ~ 15.75 V Voltage - Supply Digital 14.25 V ~ 15.75 V Voltage - Supply Digital 14.25 V ~ 15.75 V Voltage - Supply Digital 19.25 V ~ 15.75 V Voltage - Supply Digital 14.25 V ~ 15.75 V Voltage - Supply Digital 19.25 V ~ 15.75 V Voltage - Supply Digital 19.25 V ~ 15.75 V Voltage - S		
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 20-DIP (0.300", 7.62mm) Series DACPORT? Number of Bits 12 Number of D/A Converters 1 Settling Time 5µs, 10µs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±14.25 V ~ 15.75 V Voltage - Supply, Digital 14.25 V ~ 15.75 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture R-2R Operating Temperature 0°C ~ 70°C Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package 20-PDIP Mounting Type -	Manufacturer Part Number	AD7248JNZ
Package20-DIP (0.300", 7.62mm)SeriesDACPORT?Number of Bits12Number of D/A Converters1Settling Time5μs, 10μsOutput TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog±14.25 V ~ 15.75 VVoltage - Supply, Digital14.25 V ~ 15.75 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureR-2ROperating Temperature0°C ~ 70°CPackage / Case20-DIP (0.300", 7.62mm)Mounting Type-	Manufacturer	Analog Devices Inc.
Package 20-DIP (0.300", 7.62mm) Series DACPORT? Number of Bits 12 Number of D/A Converters 1 Settling Time 5μs, 10μs Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±14.25 V ~ 15.75 V Voltage - Supply, Digital 14.25 V ~ 15.75 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture R-2R Operating Temperature 0°C ~ 70°C Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package 20-PDIP Mounting Type -	Category	Integrated Circuits (ICs)
SeriesDACPORT?Number of Bits12Number of D/A Converters1Settling Time 5μ s, 10μ sOutput TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog $\pm 14.25 \text{ V} \sim 15.75 \text{ V}$ Voltage - Supply, Digital $14.25 \text{ V} \sim 15.75 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ ArchitectureR-2ROperating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Package / Case $20\text{-DIP} (0.300^{\circ}, 7.62\text{mm})$ Supplier Device Package 20-PDIP Mounting Type-		Data Acquisition - Digital to Analog Converters (DAC)
Number of Bits12Number of D/A Converters1Settling Time5μs, 10μsOutput TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog±14.25 V ~ 15.75 VVoltage - Supply, Digital14.25 V ~ 15.75 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureR-2ROperating Temperature0°C ~ 70°CPackage / Case20-DIP (0.300", 7.62mm)Supplier Device Package20-PDIPMounting Type-	Package	20-DIP (0.300", 7.62mm)
Number of D/A Converters1Settling Time5μs, 10μsOutput TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeInternalVoltage - Supply, Analog±14.25 V ~ 15.75 VVoltage - Supply, Digital14.25 V ~ 15.75 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureR-2ROperating Temperature0°C ~ 70°CPackage / Case20-DIP (0.300", 7.62mm)Supplier Device Package20-PDIPMounting Type-	Series	DACPORT?
Settling Time $5\mu s$, $10\mu s$ Output Type $Voltage - Buffered$ Differential Output No Data Interface $Parallel$ Reference Type $Internal$ Voltage - Supply, Analog $\pm 14.25 \text{ V} \sim 15.75 \text{ V}$ Voltage - Supply, Digital $14.25 \text{ V} \sim 15.75 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ Architecture $R-2R$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Package / Case $20\text{-DIP }(0.300'', 7.62\text{mm})$ Supplier Device Package M Mounting Type M	Number of Bits	12
Output Type Differential Output No Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±14.25 V ~ 15.75 V Voltage - Supply, Digital Internal 14.25 V ~ 15.75 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture R-2R Operating Temperature O°C ~ 70°C Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type -	Number of D/A Converters	1
Differential Output Data Interface Parallel Reference Type Internal Voltage - Supply, Analog ±14.25 V ~ 15.75 V Voltage - Supply, Digital INL/DNL (LSB) Architecture R-2R Operating Temperature 0°C ~ 70°C Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type -	Settling Time	5μs, 10μs
Data InterfaceParallelReference TypeInternalVoltage - Supply, Analog±14.25 V ~ 15.75 VVoltage - Supply, Digital14.25 V ~ 15.75 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureR-2ROperating Temperature0°C ~ 70°CPackage / Case20-DIP (0.300", 7.62mm)Supplier Device Package20-PDIPMounting Type-	Output Type	Voltage - Buffered
Reference TypeInternalVoltage - Supply, Analog $\pm 14.25 \text{ V} \sim 15.75 \text{ V}$ Voltage - Supply, Digital $14.25 \text{ V} \sim 15.75 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ Architecture $R-2R$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Package / Case $20-\text{DIP} (0.300'', 7.62\text{mm})$ Supplier Device Package $20-\text{PDIP}$ Mounting Type-	Differential Output	No
Voltage - Supply, Analog $\pm 14.25 \text{ V} \sim 15.75 \text{ V}$ Voltage - Supply, Digital $14.25 \text{ V} \sim 15.75 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ Architecture $R-2R$ Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Package / Case $20\text{-DIP }(0.300^{\circ}, 7.62\text{mm})$ Supplier Device Package 20-PDIP Mounting Type $-$	Data Interface	Parallel
Voltage - Supply, Digital $14.25 \text{ V} \sim 15.75 \text{ V}$ $INL/DNL \text{ (LSB)} \qquad \pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ Architecture $R-2R$ $Operating Temperature \qquad 0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ $Package / Case \qquad 20-DIP \text{ (0.300", 7.62mm)}$ $Supplier Device Package \qquad 20-PDIP$ $Mounting Type \qquad -$	Reference Type	Internal
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Voltage - Supply, Analog	±14.25 V ~ 15.75 V
Architecture R-2R Operating Temperature 0°C ~ 70°C Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package 20-PDIP Mounting Type -	Voltage - Supply, Digital	14.25 V ~ 15.75 V
Operating Temperature0°C ~ 70°CPackage / Case20-DIP (0.300", 7.62mm)Supplier Device Package20-PDIPMounting Type-	INL/DNL (LSB)	± 1 (Max), ± 1 (Max)
Package / Case 20-DIP (0.300", 7.62mm) Supplier Device Package 20-PDIP Mounting Type -	Architecture	R-2R
Supplier Device Package 20-PDIP Mounting Type -	Operating Temperature	0°C ~ 70°C
Mounting Type -	Package / Case	20-DIP (0.300", 7.62mm)
	Supplier Device Package	20-PDIP
Report errors?	Mounting Type	-
r r r		Report errors?

AD7248JNZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD7248JNZ Payment Methods



















AD7248JNZ Shipping Methods













If you have any question about AD7248JNZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com