

AD7274BUJZ-500RL7

AD7274BUJZ-500RL7 Information

theisener of		AD7274BUJZ-500RL7 Analog Devices Inc. Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) IC ADC 12BIT 3MSPS TSOT23-8	
	Package	SOT-23-8 Thin, TSOT-23-8	「回診院報告
For Referen	ce Only	For the pricing/inventory/lead time, please contact us	
	2	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AD7274BUJZ-500RL7 Specifications

Manufacturer Part NumberAD7274BUJZ-500RL7ManufacturerAnalog Devices Inc.CategoryIntegrated Circuits (ICs)Dath Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)JRJumber of Inputs1Input TypeSigle EndedData InterfaceSPI, DSPConfigurationS/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2,35 V ~ 3.6 VVoltage - Supply, Digital-Querating Temperature40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Mounting Type-Suppler Device Package-Mounting Type-Mounting Type-Mounting Type-Mounting Type-		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating Temperature-Ackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting TypeSourding Type-	Manufacturer Part Number	AD7274BUJZ-500RL7
Index Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCNumber of A/D Converters1Number of A/D Converters1ArchitectureSARReference TypeSot N - 3.6 VVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital-Pertures-Operating Temperature-Ackage / CaseSOT - 23-8Supplier Device PackageISOT - 23-8Mounting Type-Supplier Device Package-Supplier Device Package-Suppling Type-Suppling Type-	Manufacturer	Analog Devices Inc.
PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital-Features-Operating Temperature40°C ~ 125°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Category	Integrated Circuits (ICs)
Series-Number of Bits12Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital2.35 V ~ 3.6 VPeatures-Operating Temperature40°C ~ 125°CPackage / CaseSOT-23-8Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H: ADC1.1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital2.35 V ~ 3.6 VPeatures-Operating Temperature40°C ~ 125°CPackage / CaseSOT - 23-8Mounting Type-Potouring Type-	Package	SOT-23-8 Thin, TSOT-23-8
Sampling Rate (Per Second)3MNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog.35 V ~ 3.6 VVoltage - Supply, Digital.40°C ~ 125°CPackage / CaseSOT - 23.8Supplier Device Package.50T - 23.8Mounting Type.	Series	-
Number of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital2.35 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Mounting Type-	Number of Bits	12
Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating TemperatureA0°C ~ 125°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	3M
Data InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature40°C ~ 125°CPackage / CaseSOT-23-8Munting Type-	Input Type	Single Ended
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARArchitectureExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device Package-Mounting Type-	Data Interface	SPI, DSP
Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitectureSARReference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeExternalVoltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.35 V ~ 3.6 VVoltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Architecture	SAR
Voltage - Supply, Digital2.35 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Reference Type	External
Features-Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Voltage - Supply, Analog	2.35 V ~ 3.6 V
Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Voltage - Supply, Digital	2.35 V ~ 3.6 V
Package / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Features	-
Supplier Device PackageTSOT-23-8Mounting Type-	Operating Temperature	-40°C ~ 125°C
Mounting Type -	Package / Case	SOT-23-8 Thin, TSOT-23-8
	Supplier Device Package	TSOT-23-8
Report errors?	Mounting Type	-
		Report errors?

AD7274BUJZ-500RL7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

AD7274BUJZ-500RL7 Payment Methods



AD7274BUJZ-500RL7 Shipping Methods



If you have any question about AD7274BUJZ-500RL7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com