

AD7476SRTZ-REEL

AD7476SRTZ-REEL Information

unev.net.enter.com		AD7476SRTZ-REEL Analog Devices Inc. Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC 12BIT 1MSPS SOT23-6	- <u>2887295</u> 7
	Package	SOT-23-6	国 2753 号 ,
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AD7476SRTZ-REEL Specifications

Manufacturer Part NumberAD7476SRTZ-REELManufacturerAnalog Devices Inc.CategoryIntegrated Circuits (ICS)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-6Stries-Number of Bits12Sampling Rate (Per Second)00kJumber of Inputs1Input TypeSigle EndedData for Sift ACCSift ADCConfigurationS/H-ADCNumber of ADC converters1Number of ADC converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital.355 V ~ 5.25 VPortage Terrers.5°C ~ 125°CPackage (CaseSOT - 23-6Suppler Device PackageSOT - 23-6Mounting Type.Suppler Device PackageSOT - 23-6Mounting Type.Suppler Device PackageSOT - 23-6Suppler Devi		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)600kNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating Temperature-Operating TemperatureSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-Supplier Device Package-Supplier Device Package-Sourting Type-Supplier Device Package-Supplier Device Package-	Manufacturer Part Number	AD7476SRTZ-REEL
Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)600kNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Peakage / CaseSOT-215°CSupplier Device PackageSOT-23-6Mounting TypeSOT-23-6Mounting Type-	Manufacturer	Analog Devices Inc.
PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)600kNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating Temperature-Package / CaseSOT-23-6Supplier Device Package.Mounting Type-	Category	Integrated Circuits (ICs)
Series - Number of Bits 12 Sampling Rate (Per Second) 600k Number of Inputs 1 Input Type Single Ended Data Interface SPI, DSP Configuration S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Suply Voltag - Supply, Digital 2.35 V ~ 5.25 V Voltag - Supply, Digital 2.35 V ~ 5.25 V Peatures - Operating Temperature SOT - 215°C Package / Case SOT - 23-6 Supplier Device Package SOT - 23-6		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)600kNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Digital2.35 V ~ 5.25 VVoltage - Supply, Digital.55°C ~ 125°CPeaturesSOT-23-6Supplier Device PackageSOT-23-6Mounting Type.	Package	SOT-23-6
Sampling Rate (Per Second)600kNumber of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating TemperatureSOT ~ 2.35°CSupplier Device PackageSOT - 23-6Mounting Type-	Series	-
Number of Inputs1Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Digital2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating TemperatureSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Number of Bits	12
Input TypeSingle EndedData InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VYoltage - Supply, Digital-Operating Temperature-Package / CaseSOT-23-6Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	600k
Data InterfaceSPI, DSPConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package-Mounting Type-	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Mounting Type-	Input Type	Single Ended
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARArchitectureSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package-Mounting Type-	Data Interface	SPI, DSP
Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT - 23-6Supplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package-Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Architecture	SAR
Voltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Reference Type	Supply
Features-Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Voltage - Supply, Analog	2.35 V ~ 5.25 V
Operating Temperature-55°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Voltage - Supply, Digital	2.35 V ~ 5.25 V
Package / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Features	-
Supplier Device PackageSOT-23-6Mounting Type-	Operating Temperature	-55°C ~ 125°C
Mounting Type -	Package / Case	SOT-23-6
	Supplier Device Package	SOT-23-6
Report errors?	Mounting Type	-
		Report errors?

AD7476SRTZ-REEL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AD7476SRTZ-REEL Payment Methods





If you have any question about AD7476SRTZ-REEL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com