



AD7533KNZ Information



For Reference Only

Part Number AD7533KNZ

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Data Acquisition - Digital to Analog Converters

(DAC)

Description IC DAC 10BIT MULTIPLYING 16-DIP

Package 16-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD7533KNZ Specifications

Manufacturer Part Number AD7533KNZ Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 16-DIP (0.300", 7.62mm) Series - Number of Bits 10 Number of D/A Converters 1 Settling Time 800ns Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V NL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -		
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 16-DIP (0.300", 7.62mm) Series - Number of Bits 10 Number of D/A Converters 1 Settling Time 800ns Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	Manufacturer Part Number	AD7533KNZ
Package16-DIP $(0.300", 7.62mm)$ Series-Number of Bits10Number of D/A Converters1Settling Time800nsOutput TypeCurrent - UnbufferedDifferential OutputYesData InterfaceParallelReference TypeExternalVoltage - Supply, Analog $5 \text{ V} \sim 15 \text{ V}$ Voltage - Supply, Digital $5 \text{ V} \sim 15 \text{ V}$ INL/DNL (LSB)-, $\pm 1 \text{ (Max)}$ ArchitectureR-2ROperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case16-DIP $(0.300", 7.62mm)$ Mounting Type-	Manufacturer	Analog Devices Inc.
Package 16-DIP (0.300", 7.62mm) Series - Number of Bits 10 Number of D/A Converters 1 Settling Time 800ns Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	Category	Integrated Circuits (ICs)
Series - Number of Bits 10 Number of D/A Converters 1 Settling Time 800ns Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -		Data Acquisition - Digital to Analog Converters (DAC)
Number of Bits Number of D/A Converters 1 Settling Time 800ns Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - 10 10 10 10 10 10 10 10 10	Package	16-DIP (0.300", 7.62mm)
Number of D/A Converters1Settling Time800nsOutput TypeCurrent - UnbufferedDifferential OutputYesData InterfaceParallelReference TypeExternalVoltage - Supply, Analog5 V ~ 15 VVoltage - Supply, Digital5 V ~ 15 VINL/DNL (LSB)-, ±1 (Max)ArchitectureR-2ROperating Temperature-40°C ~ 85°CPackage / Case16-DIP (0.300", 7.62mm)Supplier Device Package16-PDIPMounting Type-	Series	-
Settling Time800nsOutput TypeCurrent - UnbufferedDifferential OutputYesData InterfaceParallelReference TypeExternalVoltage - Supply, Analog5 V ~ 15 VVoltage - Supply, Digital5 V ~ 15 VINL/DNL (LSB)-, ±1 (Max)ArchitectureR-2ROperating Temperature-40°C ~ 85°CPackage / Case16-DIP (0.300", 7.62mm)Supplier Device Package16-PDIPMounting Type-	Number of Bits	10
Output Type Current - Unbuffered Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	Number of D/A Converters	1
Differential Output Yes Data Interface Parallel Reference Type External Voltage - Supply, Analog Voltage - Supply, Digital INL/DNL (LSB) -, ±1 (Max) Architecture R-2R Operating Temperature Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package Mounting Type - Yes Parallel External 5 V ~ 15 V Voltage - Supply, Digital 5 V ~ 15 V -, ±1 (Max) -, ±1 (Max) -, ±1 (Max) -40°C ~ 85°C 16-DIP (0.300", 7.62mm)	Settling Time	800ns
Data InterfaceParallelReference TypeExternalVoltage - Supply, Analog5 V ~ 15 VVoltage - Supply, Digital5 V ~ 15 VINL/DNL (LSB)-, ±1 (Max)ArchitectureR-2ROperating Temperature-40°C ~ 85°CPackage / Case16-DIP (0.300", 7.62mm)Supplier Device Package16-PDIPMounting Type-	Output Type	Current - Unbuffered
Reference TypeExternalVoltage - Supply, Analog $5 \text{ V} \sim 15 \text{ V}$ Voltage - Supply, Digital $5 \text{ V} \sim 15 \text{ V}$ INL/DNL (LSB) $-, \pm 1 \text{ (Max)}$ Architecture $R-2R$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $16-\text{DIP} (0.300'', 7.62\text{mm})$ Supplier Device Package $16-\text{PDIP}$ Mounting Type $-$	Differential Output	Yes
Voltage - Supply, Analog $5 \text{ V} \sim 15 \text{ V}$ Voltage - Supply, Digital $5 \text{ V} \sim 15 \text{ V}$ INL/DNL (LSB) $-, \pm 1 \text{ (Max)}$ Architecture $R-2R$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $16-\text{DIP (0.300", 7.62mm)}$ Supplier Device Package $16-\text{PDIP}$ Mounting Type $-$	Data Interface	Parallel
Voltage - Supply, Digital $5 \text{ V} \sim 15 \text{ V}$ INL/DNL (LSB)-, $\pm 1 \text{ (Max)}$ ArchitectureR-2ROperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / Case $16\text{-DIP (0.300", 7.62mm)}$ Supplier Device Package 16-PDIP Mounting Type-	Reference Type	External
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Voltage - Supply, Analog	5 V ~ 15 V
Architecture R-2R Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	Voltage - Supply, Digital	5 V ~ 15 V
Operating Temperature -40°C ~ 85°C Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	INL/DNL (LSB)	-, ±1 (Max)
Package / Case 16-DIP (0.300", 7.62mm) Supplier Device Package 16-PDIP Mounting Type -	Architecture	R-2R
Supplier Device Package 16-PDIP Mounting Type -	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	16-DIP (0.300", 7.62mm)
	Supplier Device Package	16-PDIP
Report errors?	Mounting Type	-
		Report errors?

AD7533KNZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD7533KNZ Payment Methods



















AD7533KNZ Shipping Methods













If you have any question about AD7533KNZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com