

AD7922AUJZ-REEL7

AD7922AUJZ-REEL7 Information

verschelsener.com		AD7922AUJZ-REEL7 Analog Devices Inc. Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
100 C	Description	IC ADC DUAL 12BIT 2CH TSOT-23-8	309,823
	Package	SOT-23-8 Thin, TSOT-23-8	国際政策は
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AD7922AUJZ-REEL7 Specifications

Manufacturer Part NumberAD7922AUJZ-REEL7ManufacturerAnalog Devices Inc.CategoryIntegrated Circuits (ICS)Dath Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)IMCDyutt of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCNumber of ADC Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Jnalog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VOperating Temperature4.0°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Suppler Device PackageSOT-23-8 Thin, TSOT-23-8Mounting Type.Conting Type.		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)IMNumber of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Digital2.35 V ~ 5.25 VVoltage - Supply, Digital-Qerating Temperature-Operating Temperature-Package / CaseSOT-23-8 Thin, TSOT-23-8Munuting Type-Supplier Device Package-Mounting Type-	Manufacturer Part Number	AD7922AUJZ-REEL7
Index Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)IMNumber of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCNumber of A/D Converters1Number of A/D Converters1ArchitectureSARReferenc TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Pertures-Operating Temperature-Arckage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mutuning Type-Supplier Device Package-Supplier Device Package-Suppling Type-Suppling Type-	Manufacturer	Analog Devices Inc.
PackageSOT-23-8 Thin, TSOT-23-8Series-Number of Bits12Sampling Rate (Per Second)1MNumber of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Category	Integrated Circuits (ICs)
Series - Number of Bits 12 Sampling Rate (Per Second) IM Number of Inputs 2 Input Type Single Ended Data Interface SPI, DSP Configuration MUX-S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Supply Voltag - Supply, Digital 2.35 V ~ 5.25 V Voltag - Supply, Digital 2.35 V ~ 5.25 V Peatures - Operating Temperature 40°C ~ 85°C Package / Case SOT-23-8 Thin, TSOT-23-8 Supplier Device Package TSOT-23-8		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)IMNumber of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Digital2.35 V ~ 5.25 VVoltage - Supply, Digital.35 V ~ 5.25 VPeatures-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Mounting Type-	Package	SOT-23-8 Thin, TSOT-23-8
Sampling Rate (Per Second)IMNumber of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Packarge / CaseSOT - 2.38 °CSupplier Device PackageSOT - 2.38Mounting Type-	Series	-
Number of Inputs2Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Digital2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Mounting Type-	Number of Bits	12
Input TypeSingle EndedData InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital-Peatures-Operating TemperatureA0°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	1M
Data InterfaceSPI, DSPConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Number of Inputs	2
ConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Munting Type-	Input Type	Single Ended
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeSuplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device Package-Mounting Type-	Data Interface	SPI, DSP
Number of A/D Converters1ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device Package-Mounting Type-	Configuration	MUX-S/H-ADC
ArchitectureSARReference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeSupplyVoltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.35 V ~ 5.25 VVoltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Architecture	SAR
Voltage - Supply, Digital2.35 V ~ 5.25 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Reference Type	Supply
Features-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Voltage - Supply, Analog	2.35 V ~ 5.25 V
Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Voltage - Supply, Digital	2.35 V ~ 5.25 V
Package / CaseSOT-23-8 Thin, TSOT-23-8Supplier Device PackageTSOT-23-8Mounting Type-	Features	-
Supplier Device PackageTSOT-23-8Mounting Type-	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	SOT-23-8 Thin, TSOT-23-8
	Supplier Device Package	TSOT-23-8
Report errors?	Mounting Type	-
		Report errors?

AD7922AUJZ-REEL7 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AD7922AUJZ-REEL7 Payment Methods





If you have any question about AD7922AUJZ-REEL7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com