

AD8017ARZ-REEL

AD8017ARZ-REEL Information



For Reference Only

Part Number AD8017ARZ-REEL

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 160MHZ 8SOIC **Package** 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD8017ARZ-REEL Specifications

Manufacturer Part Number AD8017ARZ-REEL Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 1600 V/μs Gain Bandwidth Product - -3db Bandwidth 160MHz Current - Input Bias 16μA Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (±) 4.4 V ~ 12 V, ±2.2 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 1600 V/μs Gain Bandwidth Product - -3db Bandwidth 160MHz Current - Input Bias 16μA Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (±) 4.4 V ~ 12 V, ±2.2 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Manufacturer Part Number	AD8017ARZ-REEL
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate1600 V/μsGain Bandwidth Product3db Bandwidth160MHzCurrent - Input Bias16μAVoltage - Input Offset1.8mVCurrent - Supply7mACurrent - Output / Channel270mAVoltage - Supply, Single/Dual (±)4.4 V ~ 12 V, ±2.2 V ~ 6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Manufacturer	Analog Devices Inc.
Package8-SOIC (0.154", 3.90mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output Type-Slew Rate1600 V/μsGain Bandwidth Product3db Bandwidth160MHzCurrent - Input Bias16μAVoltage - Input Offset1.8mVCurrent - Supply7mACurrent - Output / Channel270mAVoltage - Supply, Single/Dual (±)4.4 V ~ 12 V, ±2.2 V ~ 6 VOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate 1600 V/μs Gain Bandwidth Product - -3db Bandwidth 160MHz Current - Input Bias 16μA Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (±) 4.4 V ~ 12 V, ±2.2 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type General Purpose Number of Circuits 2 Output Type - Slew Rate $1600 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 160MHz Current - Input Bias $16\mu\text{A}$ Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Package	8-SOIC (0.154", 3.90mm Width)
Number of Circuits 2 Output Type - Slew Rate $1600 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 160MHz Current - Input Bias $16\mu\text{A}$ Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Series	-
Output Type - Slew Rate $1600 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 160MHz Current - Input Bias $16\mu\text{A}$ Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Amplifier Type	General Purpose
Slew Rate $1600 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 160MHz Current - Input Bias $16\mu\text{A}$ Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth Current - Input Bias 16 μ A Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel Voltage - Supply, Single/Dual (\pm) Operating Temperature Mounting Type 160MHz 160MHz 160MHz 170MA 180MV 180	Output Type	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	1600 V/μs
Current - Input Bias $16\mu A$ Voltage - Input Offset $1.8mV$ Current - Supply $7mA$ Current - Output / Channel $270mA$ Voltage - Supply, Single/Dual (\pm) $4.4\ V \sim 12\ V, \pm 2.2\ V \sim 6\ V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount	Gain Bandwidth Product	-
Voltage - Input Offset 1.8mV Current - Supply 7mA Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) 4.4 V ~ 12 V, \pm 2.2 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	-3db Bandwidth	160MHz
Current - Supply $7mA$ Current - Output / Channel $270mA$ Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Current - Input Bias	16μΑ
Current - Output / Channel 270mA Voltage - Supply, Single/Dual (\pm) $4.4 \text{ V} \sim 12 \text{ V}, \pm 2.2 \text{ V} \sim 6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Input Offset	1.8mV
Voltage - Supply, Single/Dual (\pm) 4.4 V ~ 12 V, \pm 2.2 V ~ 6 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Current - Supply	7mA
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Current - Output / Channel	270mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	4.4 V ~ 12 V, ±2.2 V ~ 6 V
0 71	Operating Temperature	-40°C ~ 85°C
Package / Case 8-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Supplier Device Package 8-SOIC	Supplier Device Package	8-SOIC
Report errors		Report errors?

AD8017ARZ-REEL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD8017ARZ-REEL Payment Methods



















AD8017ARZ-REEL Shipping Methods













If you have any question about AD8017ARZ-REEL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com