

AD848SQ/883B Information



For Reference Only

Part Number AD848SQ/883B

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 175MHZ LP 8CERDIP

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AD848SQ/883B Specifications

Manufacturer Part Number Analog Devices Inc. Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package - Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate Gain Bandwidth Product 3db Bandwidth - Current - Input Bias - Voltage - Input Offset Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Package / Case Supplier Davice Package Supplier Davice Package Supplier Davice Package Instrumentation, OP Amps, Buffer Amps Function, OP Amps, Buffer Amps Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Suppliers - Amplifiers - Instrumentation, OP Amps, Buffer Amps - Supplier Suppliers - Instrumentation, OP Amps, Buffer Amps - Suppliers - Instrumentation, OP Amps - Suppliers - Instrumentation,		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package Series Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 300 V/µs Gain Bandwidth Product -3db Bandwidth - Current - Input Bias Voltage - Input Offset Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature -55°C ~ 125°C Mounting Type Package / Case Instrumentation, OP Amps, Buffer Amps Linear - Amplifiers - Instrumentation, OP Amps Amps Linear - Amplifiers - Instrumentation, OP Amps Buffer Amps Linear - Amplifiers - Instrumentation, OP Amps Buffer Amps Linear - Amplifiers - Instrumentation, OP Amps Buffer Amps - Linear - Amplifiers - Instrumentation, OP Amps Buffer Amps - Supfer Amps - Linear - Amplifiers - Instrumentation, OP Amps Buffer Amps - Supfer Amps - - Amplifier S - Instrumentation, OP Amps Buffer Amps - Supfer Amps - - Amplifier S - Instrumentation, OP Amps Buffer Amps - Supfer Amps - - Amplifier S - Instrumentation, OP Amps Buffer Amps - - - Amplifier S - Instrumentation, OP Amps - - Amplifier S - Instrumentation, OP Amps - - - Amplifier S - Instrumentation, OP Amps - - - - - - - - - - - - -	Manufacturer Part Number	AD848SQ/883B
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package - Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 300 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Manufacturer	Analog Devices Inc.
Package - Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 300 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 1 Output Type - Slew Rate 300 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 1 Output Type - Slew Rate 300 V/μs Gain Bandwidth Product3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Output / Channel Voltage - Supply, Single/Dual (±) Voltage - Supply, Single/Dual (±)55°C ~ 125°C Mounting Type - Package / Case General Purpose 1 44.5 V ~ 18 V 5.1 m A 5.1 m A 5.2 m A 5.2 m A 5.3 m A 5.4 m A 6.5 m C 6.5 m C 7.5 m C 7.5 m C 7.5 m C 7.5 m C 8.5 m C 8.5 m C 9.5 m C	Package	-
Number of Circuits 1 Output Type - Slew Rate 300 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Series	-
Output Type - Slew Rate 300 V/μs Gain Bandwidth Product - -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Number of Circuits	1
Gain Bandwidth Product -3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Output Type	-
-3db Bandwidth - Current - Input Bias - Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Slew Rate	300 V/μs
Current - Input Bias Voltage - Input Offset - Current - Supply 5.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Gain Bandwidth Product	-
Voltage - Input Offset Current - Supply 5.1mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 44.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	-3db Bandwidth	-
Current - Supply 5.1mA Current - Output / Channel 32mA Voltage - Supply, Single/Dual (±) ±4.5 V ~ 18 V Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Current - Input Bias	-
Current - Output / Channel $32mA$ Voltage - Supply, Single/Dual (±) $\pm 4.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type-Package / Case-	Voltage - Input Offset	-
Voltage - Supply, Single/Dual (\pm) $\pm 4.5 \text{ V} \sim 18 \text{ V}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Mounting Type - Package / Case -	Current - Supply	5.1mA
Operating Temperature -55°C ~ 125°C Mounting Type - Package / Case -	Current - Output / Channel	32mA
Mounting Type - Package / Case -	Voltage - Supply, Single/Dual (±)	±4.5 V ~ 18 V
Package / Case -	Operating Temperature	-55°C ~ 125°C
	Mounting Type	-
Supplier Davice Package	Package / Case	-
Supplied Device Fackage -	Supplier Device Package	-
Report errors		Report errors?

AD848SQ/883B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AD848SQ/883B Payment Methods





















AD848SQ/883B Shipping Methods













If you have any question about AD848SQ/883B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com