

AD9214BRS-65

AD9214BRS-65 Information

La Martinetter		AD9214BRS-65 Analog Devices Inc. Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
25555	Description	IC ADC 10BIT 65MSPS 28-SSOP	1979-14
	Package	28-SSOP (0.209", 5.30mm Width)	I CANAGA AND A DECEMBER OF
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AD9214BRS-65 Specifications

ManufacturerAnalog Devices Inc.CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package28-SSOP (0.209", 5.30mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H: ADC1:1Number of A/D Converters1ArchitecturePipelinedNumber of Jyp3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VVoltage - Supply, Digital-Qperating Temperature-Ackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMunuting Type-Analog Devices Inc.28-SSOP		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package28-SSOP (0.209", 5.30mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Manufacturer Part Number	AD9214BRS-65
Data Acquisition - Analog to Digital Converters (ADC)Package28-SSOP (0.209", 5.30mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeratures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Manufacturer	Analog Devices Inc.
Package28-SSOP (0.209", 5.30mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Category	Integrated Circuits (ICs)
Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeatures-Operating Temperature40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltag - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeatures-Operating Temperature40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Package	28-SSOP (0.209", 5.30mm Width)
Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package0.Mounting Type-	Series	-
Number of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Number of Bits	10
Input TypeDifferential, Single EndedInput TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Features-Operating Temperature40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	65M
Data InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Number of Inputs	1
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Input Type	Differential, Single Ended
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedArchitectureInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Data Interface	Parallel
Number of A/D Converters1ArchitecturePipelinedArchitectureInternalReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package-Mounting Type-	Configuration	S/H-ADC
ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Ratio - S/H:ADC	1:1
Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Architecture	Pipelined
Voltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Reference Type	Internal
Features-Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Voltage - Supply, Analog	2.7 V ~ 3.6 V
Operating Temperature-40°C ~ 85°CPackage / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Voltage - Supply, Digital	2.7 V ~ 3.6 V
Package / Case28-SSOP (0.209", 5.30mm Width)Supplier Device Package28-SSOPMounting Type-	Features	-
Supplier Device Package 28-SSOP Mounting Type -	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	28-SSOP (0.209", 5.30mm Width)
	Supplier Device Package	28-SSOP
Report errors?	Mounting Type	-
		Report errors?

AD9214BRS-65 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AD9214BRS-65 Payment Methods





If you have any question about AD9214BRS-65, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com