

AD9215BRUZRL7-65

AD9215BRUZRL7-65 Information

Trittitititit www.habibibir.com		AD9215BRUZRL7-65 Analog Devices Inc. Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC 10BIT 65MSPS 3V 28TSSOP	
	Package	28-TSSOP (0.173", 4.40mm Width)	国際激光
For Reference Only		For the pricing/inventory/lead time, please contact	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AD9215BRUZRL7-65 Specifications

Manufacturer Part Number AD9215BRUZRL7-65 Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) Data Acquisition - Analog to Digital Converters (ADC) Package 28-TSSOP (0.173", 4.40mm Width) Series - Number of Bits 10 Sampling Rate (Per Second) 65M Number of Inputs 1 Input Type Differential, Single Ended Data Interface Parallel Configuration S/H-ADC Number of A/D Converters 1 Architecture Pipelined Voltage - Supply, Analog 2.7 V ~ 3.3 V Voltage - Supply, Digital 2.25 V ~ 3.6 V Features - Operating Temperature - Package / Case 28-TSSOP (0.173", 4.40mm Width)			
CategoryIntegrated Circuits (ICS)Data Acquisition - Analog to Digital Converters (ADC)Package28-TSSOP (0.173", 4.40mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1Number of Supply, Analog2,7 V ~ 3.3 VVoltage - Supply, Digital2,25 V ~ 3.6 VFeatures-Operating Temperature4.0°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-Oton Supple Device Package28-TSSOPMounting Type-	Manufacturer Part Number	AD9215BRUZRL7-65	
Data Acquisition - Analog to Digital Converters (ADC)Package28-TSSOP (0.173", 4.40mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H: ADC1.1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital-Features-Operating Temperature-Package / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-Supplier Device Package-Supplier Device Package	Manufacturer	Analog Devices Inc.	
Package28-TSSOP (0.173", 4.40mm Width)Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital-Features-Operating Temperature40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Category	Integrated Circuits (ICs)	
Series-Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H: ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Digital2.27 V ~ 3.3 VVoltage - Supply, Digital-Operating Temperature40°C ~ 85°CPackage / Case2.8-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)	
Number of Bits10Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital4.0°C ~ 85°CPeatures-Operating Temperature8.TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Package	28-TSSOP (0.173", 4.40mm Width)	
Sampling Rate (Per Second)65MNumber of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital-Peatures-Operating Temperature-Package / Case827SOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Series	-	
Number of Inputs1Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Digital2.7 V ~ 3.3 VVoltage - Supply, Digital-Peatures-Operating Temperature40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Number of Bits	10	
Input TypeDifferential, Single EndedData InterfaceParallelConfigurationS/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital-Operating Temperature-Ackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	65M	
Data InterfaceParallelDonfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Number of Inputs	1	
ConfigurationS/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital.225 V ~ 3.6 VFeatures-Operating Temperature40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package.Mounting Type.	Input Type	Differential, Single Ended	
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitecturePipelinedArchitectureNinemalReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Data Interface	Parallel	
Number of A/D Converters1ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package-Mounting Type-	Configuration	S/H-ADC	
ArchitecturePipelinedReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Ratio - S/H:ADC	1:1	
Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Number of A/D Converters	1	
Voltage - Supply, Analog2.7 V ~ 3.3 VVoltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Architecture	Pipelined	
Voltage - Supply, Digital2.25 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Reference Type	Internal	
Features-Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Voltage - Supply, Analog	2.7 V ~ 3.3 V	
Operating Temperature-40°C ~ 85°CPackage / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Voltage - Supply, Digital	2.25 V ~ 3.6 V	
Package / Case28-TSSOP (0.173", 4.40mm Width)Supplier Device Package28-TSSOPMounting Type-	Features	-	
Supplier Device Package28-TSSOPMounting Type-	Operating Temperature	-40°C ~ 85°C	
Mounting Type -	Package / Case	28-TSSOP (0.173", 4.40mm Width)	
	Supplier Device Package	28-TSSOP	
Report errors?	Mounting Type	-	
		Report errors?	

AD9215BRUZRL7-65 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AD9215BRUZRL7-65 Payment Methods





If you have any question about AD9215BRUZRL7-65, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com