

# ADA600F-24-CM

### **ADA600F-24-CM Information**

	 ADA600F-24-CM Cosel USA, Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC PS - For the pricing/inventory/lead time, please contact us Wobsite: https://www.baisanar.com	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **ADA600F-24-CM Specifications**

Manufacturer Part NumberADA600F-24-CMManufacturerCosel USA, Inc.CategoryPower Supplies - External/Internal (Off-Board)ACD ConvertersACD ConvertersPackage-SeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Solation-Voltage - Solation-V		
CategoryPower Supplies - External/Internal (Off-Board)Ac DC ConvertersPackage-SeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - SoltationITE (Commercial)Voltage - IsolationSkV (300V)Efficiency6%Operating Temperature-Voltage - Soltation-FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputFeatures-Mounting Type-Size / Dimension-Xie / Dimension-<	Manufacturer Part Number	ADA600F-24-CM
AC DC Converters       Package     -       Series     ADA       Type     Enclosed       Number of Outputs     1       Voltage - Input     85 ~ 264 VAC       Voltage - Output 1     24V       Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Voltage - Solation     IFE (Commercial)       Voltage - Isolation     SiV (3000V)       Efficiency     86%       Operating Temperature     -       Operating Temperature     -       Voltage Output, DC Input Capable, PFC, Universal Input       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chasis Mount	Manufacturer	Cosel USA, Inc.
Package-SeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 6-Voltage - Output 7-Voltage - Solotion-Voltage - IsolationSkV (3000V)Efficiency86%Operating Temperature-Voltage Output, DC Input Capable, PFC, Universal InputFeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMouting TypeSiz / Dimension-Siz / Dimensio	Category	Power Supplies - External/Internal (Off-Board)
Series     ADA       Type     Enclosed       Number of Outputs     1       Voltage - Input     85 ~ 264 VAC       Voltage - Output 1     24V       Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Voltage - Output 5     -       Voltage - Output 6     -       Voltage - Output 7     -       Voltage - Solation     ITE (Commercial)       Voltage - Isolation     StV (3000V)       Efficiency     86%       Operating Temperature     Adjustabe Output Densute Capable, PFC, Universal Input       Features     Adjustabe Output, DC Input Capable, PFC, Universal Input <tr< td=""><td></td><td>AC DC Converters</td></tr<>		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Power (Wats)-Power (Wats)-Voltage - Isolation3KV (3000V)Efficiency6%Operating Temperature-Pourting Temperature-Augustable Difficulty-Stable Output, Diffi	Package	-
Number of Outputs     1       Voltage - Input     85 ~ 264 VAC       Voltage - Output 1     24V       Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Voltage - Output 5     -       Voltage - Output 4     -       Voltage - Output 4     -       Voltage - Output 4     -       Voltage - Solation     -       Voltage - Isolation     SkV (3000V)       Efficiency     86%       Operating Temperature     -10°C ~71°C (With Derating)       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chassis Mount       Size / Dinension     7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Series	ADA
Voltage - Input     85 ~ 264 VAC       Voltage - Output 1     24V       Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Voltage - Output 4     -       Voltage - Output 4     -       Current - Output (Max)     -       Power (Watts)     -       Applications     ITE (Commercial)       Voltage - Isolation     3kV (3000V)       Efficiency     86%       Operating Temperature     -10°C ~ 71°C (With Derating)       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chassis Mount       Size / Dimension     7.68°L x 5.00°W x 2.56°H (195.0mm x 127.0mm x 65.0mm)	Туре	Enclosed
Voltage - Output 1     24V       Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Current - Output (Max)     -       Power (Watts)     -       Applications     ITE (Commercial)       Voltage - Isolation     3kV (3000V)       Efficiency     86%       Operating Temperature     -10°C ~ 11°C (With Derating)       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chassis Mount       Size / Dimension     7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Number of Outputs	1
Voltage - Output 2     -       Voltage - Output 3     -       Voltage - Output 4     -       Current - Output (Max)     -       Power (Watts)     -       Applications     ITE (Commercial)       Voltage - Isolation     3kV (3000V)       Efficiency     86%       Operating Temperature     -10°C ~71°C (With Derating)       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chassis Mount       Size / Dimension     7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3     -       Voltage - Output 4     -       Current - Output (Max)     -       Power (Watts)     -       Applications     ITE (Commercial)       Voltage - Isolation     3kV (3000V)       Efficiency     86%       Operating Temperature     -10°C ~ 71°C (With Derating)       Features     Adjustable Output, DC Input Capable, PFC, Universal Input       Mounting Type     Chassis Mount       Size / Dimension     7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Output 1	24V
Voltage - Output 4-Current - Output (Max)-Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Output 2	-
Current - Output (Max)   -     Power (Wats)   -     Applications   ITE (Commercial)     Voltage - Isolation   3kV (3000V)     Efficiency   86%     Operating Temperature   -10°C ~71°C (With Derating)     Features   Adjustable Output, DC Input Capable, PFC, Universal Input     Mounting Type   Chassis Mount     Size / Dimension   7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Output 3	-
Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Output 4	-
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Current - Output (Max)	-
Voltage - Isolation3kV (3000V)Efficiency86%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Power (Watts)	-
Efficiency86%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Applications	ITE (Commercial)
Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Voltage - Isolation	3kV (3000V)
FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Efficiency	86%
Mounting TypeChassis MountSize / Dimension7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Operating Temperature	$-10^{\circ}\text{C} \sim 71^{\circ}\text{C}$ (With Derating)
Size / Dimension     7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.68" L x 5.00" W x 2.56" H (195.0mm x 127.0mm x 65.0mm)
		Report errors?

#### **ADA600F-24-CM Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **ADA600F-24-CM Payment Methods**



# **ADA600F-24-CM Shipping Methods**



If you have any question about ADA600F-24-CM, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com