

ADA750F-30-CT

ADA750F-30-CT Information

	 ADA750F-30-CT Cosel USA, Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC PS - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ADA750F-30-CT Specifications

ManufacturerCosel USA, Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Solation-Voltage - IsolationSkV (3000V)Efficiency88%Operating Temperature-FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputFeaturesChasis MountSize / Dimension-Size / Dimension-S	_			
CategoryPower Suplies - External/Internal (Off-Board)AC DC ConvertersPackageSeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output 4-Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting Type6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Manufacturer Part Number	ADA750F-30-CT		
AC DC Converters Package - Series ADA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation ITE (Commercial) Power (Watts) - Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -10°C ~ 71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.91°L x 5.00°W x 2.76° H (175.5mm x 127.0mm x 70.0mm)	Manufacturer	Cosel USA, Inc.		
Package-SeriesADATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 130VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Power (Watts)-Power (Watts)ITE (Commercial)Voltage - IsolationSkV (3000V)Efficiency88%Operating TemperatureAdjustable Output, Denating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting Type6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
ADA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Power (Watts) - Power (Watts) - Voltage - Isolation ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 8% Operating Temperature -10°C ~ 71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chasis Mount Size / Dimension 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)		AC DC Converters		
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Solation Si < (3000V)	Package	-		
Number of Outputs 1 Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -10°C ~ 71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Series	ADA		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Voltage - Output 4 - Power (Wats) - Power (Wats) - Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -10°C ~ 71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Туре	Enclosed		
Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -10°C ~71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Number of Outputs	1		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) - Power (Watts) - Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -10°C ~ 71°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Universal Input Mounting Type 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)-Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting Type6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Output 1	30V		
Voltage - Output 4-Current - Output (Max)-Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Output 2	-		
Current - Output (Max)-Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Output 3	-		
Power (Watts)-ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Current - Output (Max)	-		
Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Power (Watts)	-		
Efficiency88%Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Applications	ITE (Commercial)		
Operating Temperature-10°C ~ 71°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, DC Input Capable, PFC, Universal InputMounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Efficiency	88%		
Mounting TypeChassis MountSize / Dimension6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Operating Temperature	-10°C ~ 71°C (With Derating)		
Size / Dimension 6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Universal Input		
	Mounting Type	Chassis Mount		
Report errors	Size / Dimension	6.91" L x 5.00" W x 2.76" H (175.5mm x 127.0mm x 70.0mm)		
			Report errors?	

ADA750F-30-CT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ADA750F-30-CT Payment Methods



ADA750F-30-CT Shipping Methods



If you have any question about ADA750F-30-CT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com