

ADC12130CIWM/NOPB

ADC12130CIWM/NOPB Information

www.meisener.com	Part Number	ADC12130CIWM/NOPB	
	Manufacturer	Texas Instruments	
	Category	Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC 12BIT +SIGN 16SOIC	1.22
	Package	16-SOIC (0.295", 7.50mm Width)	- 同記後
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

ADC12130CIWM/NOPB Specifications

ManufacturerTexas InstrumentsManufacturerTexas InstrumentsCategoryData Acquisition - Analog to Digital Converters (ADC)Package16-SOIC (0.295", 7.50mm Width)Package16-SOIC (0.295", 7.50mm Width)Series-Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-Package / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC			
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)Package16-SOIC (0.295", 7.50mm Width)Series-Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCNumber of A/D Converters1Number of A/D Converters1Reference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package6-SOICMounting TypeSupplier Device Package-Supplier Device Package- <td>Manufacturer Part Number</td> <td>ADC12130CIWM/NOPB</td>	Manufacturer Part Number	ADC12130CIWM/NOPB	
Data Acquisition - Analog to Digital Converters (ADC)Package16-SOIC (0.295", 7.50mm Width)Series-Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Manufacturer	Texas Instruments	
Package16-SOIC (0.295", 7.50mm Width)Series-Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeExternalReference Type5.5 VVoltage - Supply, Digital3 V ~ 5.5 VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Category	Integrated Circuits (ICs)	
Series-Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Digital3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VPeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-		Data Acquisition - Analog to Digital Converters (ADC)	
Number of Bits12Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltag - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VPeatures-Operating Temperature40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Package	16-SOIC (0.295", 7.50mm Width)	
Sampling Rate (Per Second)114kNumber of Inputs1, 2Input TypeDifferential, Seudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1.1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Series	-	
Number of Inputs1, 2Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Number of Bits	12	
Input TypeDifferential, Pseudo-Differential, Single EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital-Peatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	114k	
Data InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Number of Inputs	1, 2	
ConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Input Type	Differential, Pseudo-Differential, Single Ended	
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Data Interface	SPI	
Number of A/D Converters1ArchitectureSARArchitectureExternalReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Configuration	MUX-S/H-ADC	
ArchitectureSARReference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package-Mounting Type-	Ratio - S/H:ADC	1:1	
Reference TypeExternalVoltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Number of A/D Converters	1	
Voltage - Supply, Analog3 V ~ 5.5 VVoltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Architecture	SAR	
Voltage - Supply, Digital3 V ~ 5.5 VFeatures-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Reference Type	External	
Features-Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Voltage - Supply, Analog	3 V ~ 5.5 V	
Operating Temperature-40°C ~ 85°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Voltage - Supply, Digital	3 V ~ 5.5 V	
Package / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOICMounting Type-	Features	-	
Supplier Device Package16-SOICMounting Type-	Operating Temperature	-40°C ~ 85°C	
Mounting Type -	Package / Case	16-SOIC (0.295", 7.50mm Width)	
	Supplier Device Package	16-SOIC	
Report errors?	Mounting Type	-	
		Report errors?	

ADC12130CIWM/NOPB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ADC12130CIWM/NOPB Payment Methods





If you have any question about ADC12130CIWM/NOPB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com