



ADP3412JR Information



For Reference Only

Part Number ADP3412JR

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC MOSFET DVR DUAL N-CH 8-SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADP3412JR Specifications

Manufacturer Part Number ADP3412JR Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) - Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 30V Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
CategoryIntegrated Circuits (ICs)Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.15 V ~ 7.5 VLogic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)-Input TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)30VRise / Fall Time (Typ)20ns, 20nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Manufacturer Part Number	ADP3412JR
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Half-Bridge Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) - Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 30V Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	ON Semiconductor
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.15 V ~ 7.5 VLogic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)-Input TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)30VRise / Fall Time (Typ)20ns, 20nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply4.15 V ~ 7.5 VLogic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)-Input TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)30VRise / Fall Time (Typ)20ns, 20nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Synchronous Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) - Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 30V Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel MOSFET Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Half-Bridge
Gate Type Voltage - Supply 4.15 V ~ 7.5 V Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Synchronous
Voltage - Supply Logic Voltage - VIL, VIH 0.8V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)-Input TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)30VRise / Fall Time (Typ)20ns, 20nsOperating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4.15 V ~ 7.5 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature O°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	-
Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature 0°C ~ 125°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature0°C ~ 125°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	High Side Voltage - Max (Bootstrap)	30V
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	20ns, 20ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	0°C ~ 125°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
Topoli Milator		Report errors?

ADP3412JR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADP3412JR Payment Methods



















ADP3412JR Shipping Methods













If you have any question about ADP3412JR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com