



# **ADQM16012 Information**



For Reference Only

Part Number ADQM16012

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 60A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ADQM16012 Specifications**

Manufacturer Part Number         ADQM16012           Manufacturer         Panasonic Electric Works           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         ADQM           Relay Type         General Purpose           Coil Type         Latching, Single Coil           Coil Current         41.7mA           Coil Voltage         12VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         60A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         -           Operate Time         20ms           Release Time         20ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPackage-SeriesADQMRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ADQM16012
Package - Series ADQM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style Pogenate Time - Power of Turn Off Hole Termination Style Power Relays, Over 2 Amps ADQM ADQM ADQM ADQM ADQM ADQM ADQM ADQM	Manufacturer	Panasonic Electric Works
Package         -           Series         ADQM           Relay Type         General Purpose           Coil Type         Latching, Single Coil           Coil Current         41.7mA           Coil Voltage         12VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         60A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         -           Operate Time         20ms           Release Time         20ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesADQMRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	ADQM
Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 60A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) -  Operate Time 20ms  Release Time 20ms  Release Time Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 60A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) -  Operate Time 20ms  Release Time 20ms  Release Time Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	41.7mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	12VDC
Switching Voltage 250VAC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) - Operate Time 20ms  Release Time 20ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  7	Contact Rating (Current)	60A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC - Max
Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	20ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

## **ADQM16012 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ADQM16012 Payment Methods**



















### **ADQM16012 Shipping Methods**













If you have any question about ADQM16012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com