



ADQM16012 Information



For Reference Only

Part Number ADQM16012

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 60A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADQM16012 Specifications

Manufacturer Part Number ADQM16012 Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series ADQM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesADQMRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ADQM16012
Package - Series ADQM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style Pogenate Time - Power of Turn Off Hole Termination Style Power Relays, Over 2 Amps ADQM ADQM ADQM ADQM ADQM ADQM ADQM ADQM	Manufacturer	Panasonic Electric Works
Package - Series ADQM Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesADQMRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current41.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)60ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	ADQM
Coil Current 41.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 60A Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	41.7mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	12VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7	Contact Rating (Current)	60A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC - Max
Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	20ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

ADQM16012 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADQM16012 Payment Methods



















ADQM16012 Shipping Methods













If you have any question about ADQM16012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com