

ADR364AUJZ-REEL7

ADR364AUJZ-REEL7 Information



For Reference Only

Part Number ADR364AUJZ-REEL7

Manufacturer Analog Devices Inc.

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SERIES 4.096V TSOT23-5

Package SOT-23-5 Thin, TSOT-23-5

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADR364AUJZ-REEL7 Specifications

Manufacturer Part Number ADR364AUJZ-REEL7 Manufacturer Analog Devices Inc. Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SOT-23-5 Thin, TSOT-23-5 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SOT-23-5 Thin, TSOT-23-5 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Manufacturer Part Number	ADR364AUJZ-REEL7
PMIC - Voltage Reference Package SOT-23-5 Thin, TSOT-23-5 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096 V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Manufacturer	Analog Devices Inc.
Package SOT-23-5 Thin, TSOT-23-5 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Category	Integrated Circuits (ICs)
Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5		PMIC - Voltage Reference
Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output5mATolerance±0.2%Temperature Coefficient25ppm/°CNoise - 0.1Hz to 10Hz8.7μVp-pNoise - 10Hz to 10kHz-Voltage - Input3.3 V ~ 15 VCurrent - Supply190μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-5 Thin, TSOT-23-5Supplier Device PackageTSOT-5	Package	SOT-23-5 Thin, TSOT-23-5
Output TypeFixedVoltage - Output (Min/Fixed)4.096VVoltage - Output (Max)-Current - Output5mATolerance±0.2%Temperature Coefficient25ppm/°CNoise - 0.1Hz to 10Hz8.7μVp-pNoise - 10Hz to 10kHz-Voltage - Input3.3 V ~ 15 VCurrent - Supply190μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-5 Thin, TSOT-23-5Supplier Device PackageTSOT-5	Series	-
Voltage - Output (Min/Fixed) 4.096V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.2% Temperature Coefficient 25ppm/°C Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Reference Type	Series
Voltage - Output (Max)-Current - Output5mATolerance±0.2%Temperature Coefficient25ppm/°CNoise - 0.1Hz to 10Hz8.7μVp-pNoise - 10Hz to 10kHz-Voltage - Input3.3 V ~ 15 VCurrent - Supply190μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-5 Thin, TSOT-23-5Supplier Device PackageTSOT-5	Output Type	Fixed
Current - Output $5mA$ Tolerance $\pm 0.2\%$ Temperature Coefficient $25ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $8.7\mu Vp-p$ Noise - $10Hz$ to $10kHz$ -Voltage - Input $3.3 \text{ V} \sim 15 \text{ V}$ Current - Supply $190\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSOT-23-5 Thin, TSOT-23-5Supplier Device PackageTSOT-5	Voltage - Output (Min/Fixed)	4.096V
Tolerance $\pm 0.2\%$ Temperature Coefficient $25ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $8.7\mu Vp-p$ Noise - $10Hz$ to $10kHz$ - 0.2% Voltage - Input 0.2% 0	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz 8.7μVp-p Noise - 10Hz to 10kHz - Voltage - Input 3.3 V ~ 15 V Current - Supply 190μA Current - Cathode Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package	Current - Output	5mA
Noise - 0.1Hz to 10Hz	Tolerance	±0.2%
Noise - 10Hz to 10kHz-Voltage - Input3.3 V ~ 15 VCurrent - Supply190μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSOT-23-5 Thin, TSOT-23-5Supplier Device PackageTSOT-5	Temperature Coefficient	25ppm/°C
Voltage - Input $3.3 \text{ V} \sim 15 \text{ V}$ Current - Supply $190\mu\text{A}$ Current - Cathode - Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Noise - 0.1Hz to 10Hz	$8.7\mu Vp-p$
Current - Supply 190µA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Noise - 10Hz to 10kHz	-
Current - Cathode Operating Temperature40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Voltage - Input	3.3 V ~ 15 V
Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Current - Supply	190μΑ
Mounting Type Surface Mount Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Current - Cathode	-
Package / Case SOT-23-5 Thin, TSOT-23-5 Supplier Device Package TSOT-5	Operating Temperature	-40°C ~ 125°C (TA)
Supplier Device Package TSOT-5	Mounting Type	Surface Mount
	Package / Case	SOT-23-5 Thin, TSOT-23-5
Report errors?	Supplier Device Package	TSOT-5
		Report errors?

ADR364AUJZ-REEL7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADR364AUJZ-REEL7 Payment Methods



















ADR364AUJZ-REEL7 Shipping Methods













If you have any question about ADR364AUJZ-REEL7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com