

ADS1000A1QDBVRQ1

ADS1000A1QDBVRQ1 Information

wew.neterner.com		ADS1000A1QDBVRQ1 Texas Instruments Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC 12BIT I2C INTRFC SOT23-6	- 18 KINSE
	Package	SOT-23-6	目に応知せ
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ADS1000A1QDBVRQ1 Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-container><table-container><table-container><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		
CategoryIntegrated Circuits (ICS)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)12Number of Inputs1Input TypeDifferential, Single EndedData InterfaceICCConfigurationPGA-ADCRatio - S/H: ADC-Number of A/D Converters1ArchitectureSigma-DeltaNumber of LypeSigma-DeltaVoltage - Supply, Analog2,7 ~ 5,5 VVoltage - Supply, Digital-40°C ~ 125°CPeraturesGOT-23-6Nupler Device PackageSOT-23-6Supplic Device PackageSOT-23-6Mounting Type-Supplic Device PackageSOT-23-6Supplic Device PackageSot-	Manufacturer Part Number	ADS1000A1QDBVRQ1
Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)128Number of Inputs1Input TypeDifferential, Single EndedData InterfaceI2CConfigurationPGA-ADCNumber of A/D Converters1ArchitectureSigma-DeltaReference TypeSipplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package.Mounting Type-	Manufacturer	Texas Instruments
PackageSOT-23-6Series-Number of Bits12Sampling Rate (Per Second)128Number of Inputs1Input TypeDifferential, Single EndedData Interface12CConfigurationPGA-ADCNumber of A/D Converters1ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital-704. Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package-Mounting Type-	Category	Integrated Circuits (ICs)
Series - Series 12 Number of Bits 128 Sampling Rate (Per Second) 1 Input Type Differential, Single Ended Input Type Differential, Single Ended Data Interface I2C Configuration PGA-ADC Ratio - S/H: ADC - Number of A/D Converters 1 Architecture Sigma-Delta Reference Type Suply Voltage - Supply, Digital 2.7 V ~ 5.5 V Serting Temperature PGA, Selectable Address Operating Temperature SOT-23-6 Supplier Device Package SOT-23-6 Supplier Device Package SOT-23-6		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits12Sampling Rate (Per Second)128Number of Inputs1Input TypeDifferential, Single EndedData Interface12CConfigurationPGA-ADCRatio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Package	SOT-23-6
Sampling Rate (Per Second)128Number of Inputs1Input TypeDifferential, Single EndedData InterfaceI2CConfigurationPGA-ADCRatio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSuplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, DigitalGGA, Selectable AddressOperating Temperature9GA, Selectable AddressPackage / CaseSOT - 23-6Supplier Device PackageSOT - 23-6Mounting Type-	Series	-
Number of Inputs1Input TypeDifferential, Single EndedData InterfaceI2CConfigurationPGA-ADCRatio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Digital2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Number of Bits	12
Input TypeDifferential, Single EndedInput TypeDifferential, Single EndedData InterfaceI2CConfigurationPGA-ADCRatio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VYoltage - Supply, DigitalPGA, Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Sampling Rate (Per Second)	128
Data InterfaceI2CData InterfacePGA-ADCConfiguration-Ratio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Mounting Type-	Number of Inputs	1
ConfigurationPGA-ADCRatio - S/H:ADC-Number of A/D Converters1ArchitectureSigma-DeltaReference TypeSuplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Munting Type-	Input Type	Differential, Single Ended
Ratio - S/H:ADC-Ratio - S/H:ADC1Number of A/D Converters1ArchitectureSigma-DeltaArchitectureSupplyReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package.Mounting Type-	Data Interface	I2C
Number of A/D Converters1ArchitectureSigma-DeltaArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device Package-Mounting Type-	Configuration	PGA-ADC
ArchitectureSigma-DeltaReference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Ratio - S/H:ADC	-
Reference TypeSupplyVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Architecture	Sigma-Delta
Voltage - Supply, Digital2.7 V ~ 5.5 VFeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Reference Type	Supply
FeaturesPGA, Selectable AddressOperating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Voltage - Supply, Analog	2.7 V ~ 5.5 V
Operating Temperature-40°C ~ 125°CPackage / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Voltage - Supply, Digital	2.7 V ~ 5.5 V
Package / CaseSOT-23-6Supplier Device PackageSOT-23-6Mounting Type-	Features	PGA, Selectable Address
Supplier Device PackageSOT-23-6Mounting Type-	Operating Temperature	-40°C ~ 125°C
Mounting Type -	Package / Case	SOT-23-6
	Supplier Device Package	SOT-23-6
Report errors?	Mounting Type	-
		Report errors?

ADS1000A1QDBVRQ1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ADS1000A1QDBVRQ1 Payment Methods



If you have any question about ADS1000A1QDBVRQ1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com