

# ADUM1201CRZ-RL7

### **ADUM1201CRZ-RL7 Information**



For Reference Only

Part Number ADUM1201CRZ-RL7

Manufacturer Analog Devices Inc.

**Category** Isolators

**Digital Isolators** 

**Description**DGTL ISO 2.5KV GEN PURP 8SOIC**Package**8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ADUM1201CRZ-RL7 Specifications**

Manufacturer Part Number         ADUM1201CRZ-RL7           Manufacturer         Analog Devices Inc.           Category         Isolators           Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.7 v ~ 5.5 v           Operating Temperature         -40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC		
Category         Isolators           Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Manufacturer Part Number	ADUM1201CRZ-RL7
Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 ∨ ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Manufacturer	Analog Devices Inc.
Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Category	Isolators
Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC		Digital Isolators
Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         1/1           Channel Type         Unidirectional           Voltage - Isolation         2500Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         45ns, 45ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Package	8-SOIC (0.154", 3.90mm Width)
Type General Purpose  Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional  Voltage - Isolation 2500Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 25Mbps  Propagation Delay tpLH / tpHL (Max) 45ns, 45ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Series	iCoupler?
Isolated Power  Number of Channels  Inputs - Side 1/Side 2  Inputs - Side 1/Side 2  Unidirectional  Voltage - Isolation  Common Mode Transient Immunity (Min)  Data Rate  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  Voltage - Supply  Operating Temperature  -40°C ~ 105°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Technology	Magnetic Coupling
Number of Channels2Inputs - Side 1/Side 21/1Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)45ns, 45nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Туре	General Purpose
Inputs - Side 1/Side 2  Channel Type  Unidirectional  Voltage - Isolation  2500Vrms  Common Mode Transient Immunity (Min)  Data Rate  25Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Isolated Power	No
Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)45ns, 45nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Number of Channels	2
Voltage - Isolation  2500Vrms  Common Mode Transient Immunity (Min)  25kV/µs  Data Rate  25Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Inputs - Side 1/Side 2	1/1
Common Mode Transient Immunity (Min)  Data Rate  25Mbps  Propagation Delay tpLH / tpHL (Max)  45ns, 45ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Channel Type	Unidirectional
Data Rate 25Mbps  Propagation Delay tpLH / tpHL (Max) 45ns, 45ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 8-SOIC (0.154", 3.90mm Width)  Supplier Device Package 8-SOIC	Voltage - Isolation	2500Vrms
Propagation Delay tpLH / tpHL (Max)  45ns, 45ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Common Mode Transient Immunity (Min)	$25kV/\mu s$
Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Data Rate	25Mbps
Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V $\sim$ 5.5 V Operating Temperature -40°C $\sim$ 105°C Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Propagation Delay tpLH / tpHL (Max)	45ns, 45ns
Voltage - Supply $ 2.7 \text{ V} \sim 5.5 \text{ V} $ Operating Temperature $ -40^{\circ}\text{C} \sim 105^{\circ}\text{C} $ Package / Case $ 8-\text{SOIC} (0.154'', 3.90 \text{mm Width}) $ Supplier Device Package $ 8-\text{SOIC} $	Pulse Width Distortion (Max)	3ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Supplier Device Package $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ 8-SOIC $(0.154^{\circ}, 3.90 \text{mm Width})$	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Voltage - Supply	2.7 V ~ 5.5 V
Supplier Device Package 8-SOIC	Operating Temperature	-40°C ~ 105°C
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

#### **ADUM1201CRZ-RL7 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ADUM1201CRZ-RL7 Payment Methods**



















### **ADUM1201CRZ-RL7 Shipping Methods**













If you have any question about ADUM1201CRZ-RL7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com