

# ADUM1280WBRZ-RL7

### **ADUM1280WBRZ-RL7 Information**



For Reference Only

Part Number ADUM1280WBRZ-RL7
Manufacturer Analog Devices Inc.

**Category** Isolators

**Digital Isolators** 

**Description** DGTL ISO 3KV 2CH GEN PURP 8SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ADUM1280WBRZ-RL7 Specifications**

Manufacturer Part Number         ADUM1280WBRZ-RL7           Manufacturer         Analog Devices Inc.           Category         Isolators           Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         2/0           Channel Type         Unidirectional           Voltage - Isolation         3000Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         35ns, 35ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 125°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC		
Category         Isolators           Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         2/0           Channel Type         Unidirectional           Voltage - Isolation         3000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         35ns, 35ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         40°C ~ 125°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Manufacturer Part Number	ADUM1280WBRZ-RL7
Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         2/0           Channel Type         Unidirectional           Voltage - Isolation         3000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         35ns, 35ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         40°C ~ 125°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Manufacturer	Analog Devices Inc.
Package         8-SOIC (0.154", 3.90mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         2/0           Channel Type         Unidirectional           Voltage - Isolation         3000Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         35ns, 35ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 125°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC	Category	Isolators
Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         2           Inputs - Side 1/Side 2         2/0           Channel Type         Unidirectional           Voltage - Isolation         3000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         25Mbps           Propagation Delay tpLH / tpHL (Max)         35ns, 35ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         3 V ~ 5.5 V           Operating Temperature         -40°C ~ 125°C           Package / Case         8-SOIC (0.154", 3.90mm Width)           Supplier Device Package         8-SOIC		Digital Isolators
Technology Type General Purpose Isolated Power Number of Channels Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate Propagation Delay tpLH / tpHL (Max) Propagation (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature Package / Case 8-SOIC (0.154", 3.90mm Width) Sumbar (Service) Sone (Service) General Purpose (Annel Purpose (No  2 (Service) Package / Case Service) No  3 (Service) Supplier Device Package Service) No  Supplier Device Package Service No  Supplier Device Package Service Serv	Package	8-SOIC (0.154", 3.90mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation3000VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)35ns, 35nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Series	iCoupler?
Isolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation3000VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)35ns, 35nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Technology	Magnetic Coupling
Number of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation3000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)35ns, 35nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Type	General Purpose
Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation3000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)35ns, 35nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Isolated Power	No
Channel TypeUnidirectionalVoltage - Isolation3000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate25MbpsPropagation Delay tpLH / tpHL (Max)35ns, 35nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Number of Channels	2
Voltage - Isolation  3000Vrms  Common Mode Transient Immunity (Min)  25kV/µs  Data Rate  25Mbps  Propagation Delay tpLH / tpHL (Max)  35ns, 35ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 125°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package	Inputs - Side 1/Side 2	2/0
Common Mode Transient Immunity (Min)  Data Rate  25Mbps  Propagation Delay tpLH / tpHL (Max)  35ns, 35ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 125°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Channel Type	Unidirectional
Data Rate 25Mbps  Propagation Delay tpLH / tpHL (Max) 35ns, 35ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 3 V ~ 5.5 V  Operating Temperature -40°C ~ 125°C  Package / Case 8-SOIC (0.154", 3.90mm Width)  Supplier Device Package 8-SOIC	Voltage - Isolation	3000Vrms
Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 125°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Common Mode Transient Immunity (Min)	$25kV/\mu s$
Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  3 V ~ 5.5 V  Operating Temperature  -40°C ~ 125°C  Package / Case  8-SOIC (0.154", 3.90mm Width)  Supplier Device Package  8-SOIC	Data Rate	25Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $3 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $8\text{-SOIC}$ ( $0.154^{\circ}$ , $3.90 \text{mm}$ Width)Supplier Device Package $8\text{-SOIC}$	Propagation Delay tpLH / tpHL (Max)	35ns, 35ns
Voltage - Supply $3\ V \sim 5.5\ V$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $8\text{-SOIC }(0.154^{\circ}\text{, }3.90\text{mm Width})$ Supplier Device Package $8\text{-SOIC}$	Pulse Width Distortion (Max)	3ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Supplier Device Package $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ 8-SOIC $(0.154^{\circ}, 3.90 \text{mm Width})$	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Voltage - Supply	3 V ~ 5.5 V
Supplier Device Package 8-SOIC	Operating Temperature	-40°C ~ 125°C
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

### **ADUM1280WBRZ-RL7 Guarantees**



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ADUM1280WBRZ-RL7 Payment Methods**



















## ADUM1280WBRZ-RL7 Shipping Methods













If you have any question about ADUM1280WBRZ-RL7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com