



## **ADUM1311ARWZ Information**



For Reference Only

Part Number ADUM1311ARWZ
Manufacturer Analog Devices Inc.

**Category** Isolators

**Digital Isolators** 

**Description** DGTL ISO 3.75KV GEN PURP 16SOIC

**Package** 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ADUM1311ARWZ Specifications**

Manufacturer Part Number         ADUMI311ARWZ           Manufacturer         Analog Devices Inc.           Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         3           Inputs - Side 1/Side 2         2/1           Channel Type         Unidirectional           Voltage - Isolation         3750Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         1Mbps           Propagation Delay tpLH / tpHL (Max)         100ns, 100ns           Pulse Width Distortion (Max)         40ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC (0.295", 7.50mm Width)		
Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         3           Inputs - Side 1/Side 2         2/1           Channel Type         Unidirectional           Voltage - Isolation         3750Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         1Mbps           Propagation Delay tpLH / tpHL (Max)         100ns, 100ns           Pulse Width Distortion (Max)         40ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Manufacturer Part Number	ADUM1311ARWZ
Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         3           Inputs - Side 1/Side 2         2/1           Channel Type         Unidirectional           Voltage - Isolation         3750Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         1Mbps           Propagation Delay tpLH / tpHL (Max)         100ns, 100ns           Pulse Width Distortion (Max)         40ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Manufacturer	Analog Devices Inc.
Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         3           Inputs - Side 1/Side 2         2/1           Channel Type         Unidirectional           Voltage - Isolation         3750Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         1Mbps           Propagation Delay tpLH / tpHL (Max)         100ns, 100ns           Pulse Width Distortion (Max)         40ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC	Category	Isolators
SeriesiCoupler?TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels3Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC		Digital Isolators
TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels3Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Package	16-SOIC (0.295", 7.50mm Width)
Type General Purpose  Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional  Voltage - Isolation 3750Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 1Mbps  Propagation Delay tpLH / tpHL (Max) 100ns, 100ns  Pulse Width Distortion (Max) 40ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Series	iCoupler?
Isolated PowerNoNumber of Channels3Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Technology	Magnetic Coupling
Number of Channels3Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Type	General Purpose
Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Isolated Power	No
Channel Type  Voltage - Isolation  3750Vrms  Common Mode Transient Immunity (Min)  Data Rate  1Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  Voltage - Supply  Operating Temperature  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Number of Channels	3
Voltage - Isolation 3750Vrms  Common Mode Transient Immunity (Min) 25kV/ $\mu$ s  Data Rate 1Mbps  Propagation Delay tpLH / tpHL (Max) 100ns, 100ns  Pulse Width Distortion (Max) 40ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	2/1
Common Mode Transient Immunity (Min)  Data Rate  1Mbps  Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Channel Type	Unidirectional
Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	3750Vrms
Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package	Common Mode Transient Immunity (Min)	$25kV/\mu s$
Pulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Data Rate	1Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ ( $0.295^{\circ}$ , $7.50 \text{mm}$ Width)Supplier Device Package $16\text{-SOIC}$	Propagation Delay tpLH / tpHL (Max)	100ns, 100ns
Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC} (0.295'', 7.50 \text{mm Width})$ Supplier Device Package $16\text{-SOIC}$	Pulse Width Distortion (Max)	40ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ (0.295", 7.50mm Width) Supplier Device Package $16\text{-SOIC}$	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	2.7 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 105°C
	Package / Case	16-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

### **ADUM1311ARWZ Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ADUM1311ARWZ Payment Methods**



















## **ADUM1311ARWZ Shipping Methods**













If you have any question about ADUM1311ARWZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com