



ADUM140D0BRZ Information



For Reference Only

Part Number ADUM140D0BRZ
Manufacturer Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 3.75KV GEN PURP 16-SOIC

Package 16-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM140D0BRZ Specifications

Manufacturer Part Number ADUMI40D0BRZ Manufacturer Analog Devices Inc. Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		
Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer Part Number	ADUM140D0BRZ
Package 16-SOIC (0.154", 3.90mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer	Analog Devices Inc.
Package 16-SOIC (0.154", 3.90mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Category	Isolators
Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		Digital Isolators
TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation3750 VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Package	16-SOIC (0.154", 3.90mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Series	iCoupler?
Isolated Power Number of Channels Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC No 4/0 Unidirectional 4/0 Unidirectional 3750Vrms 75kV/µs 175kV/µs 150Mbps 150Mbps 13ns, 13ns 13ns, 13ns 13ns, 13ns 13ns 13ns 13ns 14ns 15ns 15ns	Technology	Magnetic Coupling
Number of Channels4Inputs - Side 1/Side 2 $4/0$ Channel TypeUnidirectionalVoltage - Isolation $3750Vrms$ Common Mode Transient Immunity (Min) $75kV/\mu s$ Data Rate $150Mbps$ Propagation Delay tpLH / tpHL (Max) $13ns, 13ns$ Pulse Width Distortion (Max) $3ns$ Rise / Fall Time (Typ) $2.5ns, 2.5ns$ Voltage - Supply $1.7 V \sim 5.5 V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Package / Case $16-SOIC$ (0.154° , $3.90mm$ Width)Supplier Device Package $16-SOIC$	Туре	General Purpose
Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Channels	4
Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/ μ s Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	4/0
Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	3750Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	75kV/μs
Pulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Data Rate	150Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.154° , 3.90mm Width)Supplier Device Package 16-SOIC	Propagation Delay tpLH / tpHL (Max)	13ns, 13ns
Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $16\text{-SOIC } (0.154^{\circ}\text{H}, 3.90 \text{mm Width})$ Supplier Device Package 16-SOIC	Pulse Width Distortion (Max)	3ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	1.7 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 125°C
	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

ADUM140D0BRZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM140D0BRZ Payment Methods





















ADUM140D0BRZ Shipping Methods













If you have any question about ADUM140D0BRZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com