

ADUM226N0WBRIZ

ADUM226N0WBRIZ Information



For Reference Only

Part Number ADUM226N0WBRIZ

Manufacturer Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 5KV 2CH GEN PURP 8SOIC

Package 8-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM226N0WBRIZ Specifications

Manufacturer Part Number ADUM226NOWBRIZ Manufacturer Analog Devices Inc. Category Isolators Package 8-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC		
Category Isolators Package 8-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Manufacturer Part Number	ADUM226N0WBRIZ
Package 8-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Manufacturer	Analog Devices Inc.
Package 8-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Category	Isolators
Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 1/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC		Digital Isolators
TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 2 $1/1$ Channel TypeUnidirectionalVoltage - Isolation $5000Vrms$ Common Mode Transient Immunity (Min) $75kV/\mu s$ Data Rate $150Mbps$ Propagation Delay tpLH / tpHL (Max) $13ns, 13ns$ Pulse Width Distortion (Max) $3ns$ Rise / Fall Time (Typ) $2.5ns, 2.5ns$ Voltage - Supply $1.7 V \sim 5.5 V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Package / Case $8-SOIC (0.295^{\circ}, 7.50mm Width)$ Supplier Device Package $8-SOIC-IC$	Package	8-SOIC (0.295", 7.50mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 21/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)75kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.295", 7.50mm Width)Supplier Device Package8-SOIC-IC	Series	iCoupler?
Isolated PowerNoNumber of Channels2Inputs - Side 1/Side 2 $1/1$ Channel TypeUnidirectionalVoltage - Isolation $5000Vrms$ Common Mode Transient Immunity (Min) $75kV/\mu s$ Data Rate $150Mbps$ Propagation Delay tpLH / tpHL (Max) $13ns, 13ns$ Pulse Width Distortion (Max) $3ns$ Rise / Fall Time (Typ) $2.5ns, 2.5ns$ Voltage - Supply $1.7 V \sim 5.5 V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Package / Case $8-SOIC (0.295^{\circ}, 7.50mm Width)$ Supplier Device Package $8-SOIC-IC$	Technology	Magnetic Coupling
Number of Channels2Inputs - Side 1/Side 21/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.295", 7.50mm Width)Supplier Device Package8-SOIC-IC	Type	General Purpose
Inputs - Side 1/Side 21/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.295", 7.50mm Width)Supplier Device Package8-SOIC-IC	Isolated Power	No
Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case8-SOIC (0.295", 7.50mm Width)Supplier Device Package8-SOIC-IC	Number of Channels	2
Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package	Inputs - Side 1/Side 2	1/1
Common Mode Transient Immunity (Min) 75kV/ μ s Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Channel Type	Unidirectional
Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Voltage - Isolation	5000Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Common Mode Transient Immunity (Min)	75kV/μs
Pulse Width Distortion (Max) $3ns$ Rise / Fall Time (Typ) $2.5ns, 2.5ns$ Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 8-SOIC (0.295° , 7.50mm Width)Supplier Device Package 8-SOIC-IC	Data Rate	150Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 8-SOIC (0.295° , 7.50mm Width)Supplier Device Package 8-SOIC-IC	Propagation Delay tpLH / tpHL (Max)	13ns, 13ns
Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $8\text{-SOIC (0.295'', 7.50mm Width)}$ Supplier Device Package 8-SOIC-IC	Pulse Width Distortion (Max)	3ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Supplier Device Package $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ 8-SOIC (0.295", 7.50mm Width) $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 8-SOIC (0.295", 7.50mm Width) Supplier Device Package 8-SOIC-IC	Voltage - Supply	1.7 V ~ 5.5 V
Supplier Device Package 8-SOIC-IC	Operating Temperature	-40°C ~ 125°C
	Package / Case	8-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	8-SOIC-IC
		Report errors?

ADUM226N0WBRIZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM226N0WBRIZ Payment Methods





















ADUM226N0WBRIZ Shipping Methods













If you have any question about ADUM226N0WBRIZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com