

ADUM2280CRIZ-RL

ADUM2280CRIZ-RL Information



For Reference Only

Part Number ADUM2280CRIZ-RL Manufacturer Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 5KV 2CH GEN PURP 16SOIC

Package 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM2280CRIZ-RL Specifications

Manufacturer Part Number ADUM2280CRIZ-RL Manufacturer Analog Devices Inc. Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC		
Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC	Manufacturer Part Number	ADUM2280CRIZ-RL
Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC	Manufacturer	Analog Devices Inc.
Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC	Category	Isolators
Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 2 Inputs - Side 1/Side 2 2/0 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC		Digital Isolators
TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)24ns, 24nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Package	16-SOIC (0.295", 7.50mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)24ns, 24nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Series	iCoupler?
Isolated PowerNoNumber of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)24ns, 24nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Technology	Magnetic Coupling
Number of Channels2Inputs - Side 1/Side 22/0Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate100MbpsPropagation Delay tpLH / tpHL (Max)24ns, 24nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Туре	General Purpose
Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Number of Channels	2
Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) 24ns, 24ns Pulse Width Distortion (Max) 2ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC	Inputs - Side 1/Side 2	2/0
Common Mode Transient Immunity (Min) Data Rate 100Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate100MbpsPropagation Delay tpLH / tpHL (Max)24ns, 24nsPulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Voltage - Isolation	5000Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	25kV/μs
Pulse Width Distortion (Max)2nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC-IC	Data Rate	100Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.295° , 7.50mm Width)Supplier Device Package 16-SOIC-IC	Propagation Delay tpLH / tpHL (Max)	24ns, 24ns
Voltage - Supply $ 2.7 \text{ V} \sim 5.5 \text{ V} $ Operating Temperature $ -40^{\circ}\text{C} \sim 125^{\circ}\text{C} $ Package / Case $ 16\text{-SOIC (0.295'', 7.50mm Width)} $ Supplier Device Package $ 16\text{-SOIC-IC} $	Pulse Width Distortion (Max)	2ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $16\text{-SOIC} (0.295^{\circ}, 7.50 \text{mm Width})$ Supplier Device Package 16-SOIC-IC	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC-IC	Voltage - Supply	2.7 V ~ 5.5 V
Supplier Device Package 16-SOIC-IC	Operating Temperature	-40°C ~ 125°C
	Package / Case	16-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	16-SOIC-IC
		Report errors?

ADUM2280CRIZ-RL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM2280CRIZ-RL Payment Methods



















ADUM2280CRIZ-RL Shipping Methods













If you have any question about ADUM2280CRIZ-RL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com