



### **ADUM2402BRWZ Information**



For Reference Only

Part Number ADUM2402BRWZ
Manufacturer Analog Devices Inc.

**Category** Isolators

**Digital Isolators** 

**Description** DGTL ISO 5KV 4CH GEN PURP 16SOIC

**Package** 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ADUM2402BRWZ Specifications**

| Manufacturer Part Number         ADUM2402BRWZ           Manufacturer         Analog Devices Inc.           Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC (0.295", 7.50mm Width) |                                      |                                |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--------------------------------|
| Category         Isolators           Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC                                                                                                                                   | Manufacturer Part Number             | ADUM2402BRWZ                   |
| Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/µs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC                                                                                                                                                                       | Manufacturer                         | Analog Devices Inc.            |
| Package         16-SOIC (0.295", 7.50mm Width)           Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC                                                                                                                                                                       | Category                             | Isolators                      |
| Series         iCoupler?           Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC                                                                                                                                                                                                                                |                                      | Digital Isolators              |
| Technology         Magnetic Coupling           Type         General Purpose           Isolated Power         No           Number of Channels         4           Inputs - Side 1/Side 2         2/2           Channel Type         Unidirectional           Voltage - Isolation         5000Vrms           Common Mode Transient Immunity (Min)         25kV/μs           Data Rate         10Mbps           Propagation Delay tpLH / tpHL (Max)         50ns, 50ns           Pulse Width Distortion (Max)         3ns           Rise / Fall Time (Typ)         2.5ns, 2.5ns           Voltage - Supply         2.7 V ~ 5.5 V           Operating Temperature         -40°C ~ 105°C           Package / Case         16-SOIC (0.295", 7.50mm Width)           Supplier Device Package         16-SOIC                                                                                                                                                                                                                                                                   | Package                              | 16-SOIC (0.295", 7.50mm Width) |
| Type General Purpose  Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 2/2 Channel Type Unidirectional  Voltage - Isolation 5000Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 10Mbps  Propagation Delay tpLH / tpHL (Max) 50ns, 50ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Series                               | iCoupler?                      |
| Isolated Power  Number of Channels  4 Inputs - Side 1/Side 2 Channel Type Unidirectional  Voltage - Isolation S000Vrms Common Mode Transient Immunity (Min) Data Rate 10Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 2.7 V ~ 5.5 V Operating Temperature Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Technology                           | Magnetic Coupling              |
| Number of Channels4Inputs - Side 1/Side 2 $2/2$ Channel TypeUnidirectionalVoltage - Isolation $5000Vrms$ Common Mode Transient Immunity (Min) $25kV/\mu s$ Data Rate $10Mbps$ Propagation Delay tpLH / tpHL (Max) $50ns$ , $50ns$ Pulse Width Distortion (Max) $3ns$ Rise / Fall Time (Typ) $2.5ns$ , $2.5ns$ Voltage - Supply $2.7 V \sim 5.5 V$ Operating Temperature $-40^{\circ}C \sim 105^{\circ}C$ Package / Case $16-SOIC$ ( $0.295^{\circ}$ , $7.50mm$ Width)Supplier Device Package $16-SOIC$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Type                                 | General Purpose                |
| Inputs - Side 1/Side 22/2Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate10MbpsPropagation Delay tpLH / tpHL (Max)50ns, 50nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Isolated Power                       | No                             |
| Channel Type Voltage - Isolation 5000Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 10Mbps Propagation Delay tpLH / tpHL (Max) 50ns, 50ns  Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Number of Channels                   | 4                              |
| Voltage - Isolation 5000Vrms  Common Mode Transient Immunity (Min) 25kV/µs  Data Rate 10Mbps  Propagation Delay tpLH / tpHL (Max) 50ns, 50ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package 16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Inputs - Side 1/Side 2               | 2/2                            |
| Common Mode Transient Immunity (Min)  Data Rate  10Mbps  Propagation Delay tpLH / tpHL (Max)  50ns, 50ns  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Channel Type                         | Unidirectional                 |
| Data Rate 10Mbps  Propagation Delay tpLH / tpHL (Max) 50ns, 50ns  Pulse Width Distortion (Max) 3ns  Rise / Fall Time (Typ) 2.5ns, 2.5ns  Voltage - Supply 2.7 V ~ 5.5 V  Operating Temperature -40°C ~ 105°C  Package / Case 16-SOIC (0.295", 7.50mm Width)  Supplier Device Package 16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Voltage - Isolation                  | 5000Vrms                       |
| Propagation Delay tpLH / tpHL (Max)  Pulse Width Distortion (Max)  Rise / Fall Time (Typ)  2.5ns, 2.5ns  Voltage - Supply  2.7 V ~ 5.5 V  Operating Temperature  -40°C ~ 105°C  Package / Case  16-SOIC (0.295", 7.50mm Width)  Supplier Device Package                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Common Mode Transient Immunity (Min) | $25kV/\mu s$                   |
| Pulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply2.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Data Rate                            | 10Mbps                         |
| Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $2.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ ( $0.295^{\circ}$ , $7.50 \text{mm}$ Width)Supplier Device Package $16\text{-SOIC}$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Propagation Delay tpLH / tpHL (Max)  | 50ns, 50ns                     |
| Voltage - Supply $ 2.7 \text{ V} \sim 5.5 \text{ V} $ Operating Temperature $ -40^{\circ}\text{C} \sim 105^{\circ}\text{C} $ Package / Case $ 16\text{-SOIC} (0.295'', 7.50 \text{mm Width}) $ Supplier Device Package $ 16\text{-SOIC} $                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Pulse Width Distortion (Max)         | 3ns                            |
| Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC}$ (0.295", 7.50mm Width) Supplier Device Package $16\text{-SOIC}$                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Rise / Fall Time (Typ)               | 2.5ns, 2.5ns                   |
| Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Voltage - Supply                     | 2.7 V ~ 5.5 V                  |
| Supplier Device Package 16-SOIC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Operating Temperature                | -40°C ~ 105°C                  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Package / Case                       | 16-SOIC (0.295", 7.50mm Width) |
| Report errors?                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Supplier Device Package              | 16-SOIC                        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                      | Report errors?                 |

#### **ADUM2402BRWZ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ADUM2402BRWZ Payment Methods**





















# **ADUM2402BRWZ Shipping Methods**













If you have any question about ADUM2402BRWZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com