



ADUM3471WARSZ Information



For Reference Only

Part Number ADUM3471WARSZ Manufacturer Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 2.5KV GEN PURP 20SSOP **Package** 20-SSOP (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM3471WARSZ Specifications

Manufacturer Part Number ADUM3471WARSZ Manufacturer Analog Devices Inc. Category Isolators Package 20-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate IMbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature 40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP		
Category Isolators Package 20-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 250Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Manufacturer Part Number	ADUM3471WARSZ
Package 20-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Manufacturer	Analog Devices Inc.
Package 20-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Category	Isolators
Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP		Digital Isolators
Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Package	20-SSOP (0.209", 5.30mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 3.6 V, 4.5 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Series	iCoupler?
Isolated PowerNoNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 3.6 V, 4.5 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Technology	Magnetic Coupling
Number of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 3.6 V, 4.5 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Туре	General Purpose
Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation2500VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 3.6 V, 4.5 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Isolated Power	No
Channel TypeUnidirectionalVoltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) $25kV/\mu s$ Data Rate $1Mbps$ Propagation Delay tpLH / tpHL (Max) $100ns, 100ns$ Pulse Width Distortion (Max) $40ns$ Rise / Fall Time (Typ) $2.5ns, 2.5ns$ Voltage - Supply $3 V \sim 3.6 V, 4.5 V \sim 5.5 V$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 20-SSOP (0.209", 5.30mm Width)Supplier Device Package 20-SSOP	Number of Channels	4
Voltage - Isolation 2500Vrms Common Mode Transient Immunity (Min) 25kV/ μ s Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Inputs - Side 1/Side 2	3/1
Common Mode Transient Immunity (Min) Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Voltage - Isolation	2500Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	$25kV/\mu s$
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 3.6 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package	Data Rate	1Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $3 \text{ V} \sim 3.6 \text{ V}, 4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 20-SSOP (0.209° , 5.30mm Width)Supplier Device Package 20-SSOP	Propagation Delay tpLH / tpHL (Max)	100ns, 100ns
Voltage - Supply $3\ V \sim 3.6\ V, 4.5\ V \sim 5.5\ V$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $20\text{-SSOP}\ (0.209'', 5.30\text{mm Width})$ Supplier Device Package 20-SSOP	Pulse Width Distortion (Max)	40ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $20\text{-SSOP} (0.209^{\circ}, 5.30 \text{mm Width})$ Supplier Device Package 20-SSOP	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 20-SSOP (0.209", 5.30mm Width) Supplier Device Package 20-SSOP	Voltage - Supply	3 V ~ 3.6 V, 4.5 V ~ 5.5 V
Supplier Device Package 20-SSOP	Operating Temperature	-40°C ~ 105°C
	Package / Case	20-SSOP (0.209", 5.30mm Width)
Report errors?	Supplier Device Package	20-SSOP
		Report errors?

ADUM3471WARSZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM3471WARSZ Payment Methods



















ADUM3471WARSZ Shipping Methods













If you have any question about ADUM3471WARSZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com