

ADUM4401ARWZ-RL

ADUM4401ARWZ-RL Information



For Reference Only

Part Number ADUM4401ARWZ-RL **Manufacturer** Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 5KV 4CH GEN PURP 16SOIC

Package 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM4401ARWZ-RL Specifications

Manufacturer Part Number ADUM4401ARWZ-RL Manufacturer Analog Devices Inc. Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature 40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC (0.295", 7.50mm Width)		
Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Manufacturer Part Number	ADUM4401ARWZ-RL
Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Manufacturer	Analog Devices Inc.
Package 16-SOIC (0.295", 7.50mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/μs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Category	Isolators
SeriesiCoupler?TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC		Digital Isolators
TechnologyMagnetic CouplingTypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Package	16-SOIC (0.295", 7.50mm Width)
Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Series	iCoupler?
Isolated PowerNoNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/µsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Technology	Magnetic Coupling
Number of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Туре	General Purpose
Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)25kV/μsData Rate1MbpsPropagation Delay tpLH / tpHL (Max)100ns, 100nsPulse Width Distortion (Max)40nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Isolated Power	No
Channel Type Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/µs Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Number of Channels	4
Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 25kV/ μ s Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	3/1
Common Mode Transient Immunity (Min) Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 1Mbps Propagation Delay tpLH / tpHL (Max) 100ns, 100ns Pulse Width Distortion (Max) 40ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	5000Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	25kV/μs
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 3 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Data Rate	1Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $3 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 16-SOIC (0.295", 7.50mm Width)Supplier Device Package 16-SOIC	Propagation Delay tpLH / tpHL (Max)	100ns, 100ns
Voltage - Supply $3 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 16-SOIC $(0.295^{\circ}, 7.50 \text{mm Width})$ Supplier Device Package 16-SOIC	Pulse Width Distortion (Max)	40ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	3 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 105°C
	Package / Case	16-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

ADUM4401ARWZ-RL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM4401ARWZ-RL Payment Methods





















ADUM4401ARWZ-RL Shipping Methods













If you have any question about ADUM4401ARWZ-RL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com