



ADUM6411BRSZ Information



For Reference Only

Part Number ADUM6411BRSZ
Manufacturer Analog Devices Inc.

Category Isolators

Digital Isolators

Description DGTL ISO 3.75KV 4CH 24SSOP **Package** 24-SSOP (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ADUM6411BRSZ Specifications

Manufacturer Part Number ADUM6411BRSZ Manufacturer Analog Devices Inc. Category Isolators Package 24-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP		
Category Isolators Package 24-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature 40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Manufacturer Part Number	ADUM6411BRSZ
Package 24-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Manufacturer	Analog Devices Inc.
Package 24-SSOP (0.209", 5.30mm Width) Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Category	Isolators
Series iCoupler? Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP		Digital Isolators
Technology Magnetic Coupling Type General Purpose Isolated Power Yes Number of Channels 4 Inputs - Side 1/Side 2 3/1 Channel Type Unidirectional Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/μs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Package	24-SSOP (0.209", 5.30mm Width)
TypeGeneral PurposeIsolated PowerYesNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case24-SSOP (0.209", 5.30mm Width)Supplier Device Package24-SSOP	Series	iCoupler?
Isolated PowerYesNumber of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)75kV/µsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case24-SSOP (0.209", 5.30mm Width)Supplier Device Package24-SSOP	Technology	Magnetic Coupling
Number of Channels4Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case24-SSOP (0.209", 5.30mm Width)Supplier Device Package24-SSOP	Туре	General Purpose
Inputs - Side 1/Side 23/1Channel TypeUnidirectionalVoltage - Isolation3750VrmsCommon Mode Transient Immunity (Min)75kV/μsData Rate150MbpsPropagation Delay tpLH / tpHL (Max)13ns, 13nsPulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case24-SSOP (0.209", 5.30mm Width)Supplier Device Package24-SSOP	Isolated Power	Yes
Channel Type Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package	Number of Channels	4
Voltage - Isolation 3750Vrms Common Mode Transient Immunity (Min) 75kV/µs Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Inputs - Side 1/Side 2	3/1
Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 13ns, 13ns Pulse Width Distortion (Max) 3ns Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Voltage - Isolation	3750Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2.5ns, 2.5ns Voltage - Supply 1.7 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	75kV/μs
Pulse Width Distortion (Max)3nsRise / Fall Time (Typ)2.5ns, 2.5nsVoltage - Supply1.7 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case24-SSOP (0.209", 5.30mm Width)Supplier Device Package24-SSOP	Data Rate	150Mbps
Rise / Fall Time (Typ) $2.5 \text{ns}, 2.5 \text{ns}$ Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 24-SSOP (0.209° , 5.30mm Width)Supplier Device Package 24-SSOP	Propagation Delay tpLH / tpHL (Max)	13ns, 13ns
Voltage - Supply $1.7 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $24\text{-SSOP} (0.209'', 5.30 \text{mm Width})$ Supplier Device Package 24-SSOP	Pulse Width Distortion (Max)	3ns
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Rise / Fall Time (Typ)	2.5ns, 2.5ns
Package / Case 24-SSOP (0.209", 5.30mm Width) Supplier Device Package 24-SSOP	Voltage - Supply	1.7 V ~ 5.5 V
Supplier Device Package 24-SSOP	Operating Temperature	-40°C ~ 105°C
	Package / Case	24-SSOP (0.209", 5.30mm Width)
Report errors?	Supplier Device Package	24-SSOP
		Report errors?

ADUM6411BRSZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ADUM6411BRSZ Payment Methods



















ADUM6411BRSZ Shipping Methods













If you have any question about ADUM6411BRSZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com