



AEH20F24N Information



For Reference Only

Part Number AEH20F24N

ManufacturerArtesyn Embedded TechnologiesCategoryPower Supplies - Board Mount

DC DC Converters

Description CONV DC-DC 100W 24VIN 3.3V NEGEN

Package 9-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AEH20F24N Specifications

Manufacturer Artesyn Embedded Technologies Category Power Supplies - Board Mount DC DC Converters Package 9-DIP Module Series AEH20 Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C		
Category Power Supplies - Board Mount DC DC Converters Package 9-DIP Module Series AEH20 Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Manufacturer Part Number	AEH20F24N
Package 9-DIP Module Series AEH20 Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Manufacturer	Artesyn Embedded Technologies
Package 9-DIP Module Series AEH20 Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Category	Power Supplies - Board Mount
Series AEH20 Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C		DC DC Converters
Type Non-Isolated PoL Module Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Package	9-DIP Module
Number of Outputs 1 Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Series	AEH20
Voltage - Input (Min) 18V Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Туре	Non-Isolated PoL Module
Voltage - Input (Max) 36V Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 66W Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Number of Outputs	1
Voltage - Output 1 Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications Features Remote On/Off Operating Temperature 3.3V 3.3V 3.3V - Current - Output (Max) - Cu	Voltage - Input (Min)	18V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Voltage - Input (Max)	36V
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) Power (Watts) Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 66W Voltage - Isolation Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Voltage - Output 3	-
Power (Watts) $66W$ Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Voltage - Output 4	-
Voltage - Isolation - Applications ITE (Commercial) Features Remote On/Off Operating Temperature -40°C ~ 100°C	Current - Output (Max)	20A
Applications ITE (Commercial) Features Remote On/Off Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Power (Watts)	66W
Features Remote On/Off Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Voltage - Isolation	-
Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$	Applications	ITE (Commercial)
	Features	Remote On/Off
Efficiency 87%	Operating Temperature	-40°C ~ 100°C
	Efficiency	87%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case 9-DIP Module	Package / Case	9-DIP Module
Size / Dimension 2.40" L x 2.30" W x 0.50" H (61.0mm x 58.4mm x 12.7mm)	Size / Dimension	2.40" L x 2.30" W x 0.50" H (61.0mm x 58.4mm x 12.7mm)

Supplier Device Package	-
Control Features	Enable, Active Low
	Report errors?

AEH20F24N Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AEH20F24N Payment Methods



















AEH20F24N Shipping Methods













If you have any question about AEH20F24N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com