



AEL15US12 Information



For Reference Only

Part Number AEL15US12 Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 15W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AEL15US12 Specifications

Manufacturer Part Number AEL15US12 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AEL Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output (Max) 1.25 A Power (Watts) 15W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AEL Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension Package - RETERING ABL AEL AEL AEL AEL AEL AEL AEL	Manufacturer Part Number	AEL15US12
Package Series AEL Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption SolomW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension AEL AEL AEL AEL AEL AEL AEL AE	Manufacturer	XP Power
Package - Series AEL Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesAELRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.25APower (Watts)15WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature-20°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)1.25APower (Watts)15WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature-20°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Series	AEL
Input Type Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension Cord (Sold Separately) 90 ~ 264 VAC 12V 12V 12V 12V 12V 12V 15W 15W 15W 15W 15W 15W 15W 15	Region Utilized	International
Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 1.25A Power (Watts) 15W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Form	Desktop (Class I)
Voltage - Output (Max) 1.25A Power (Watts) No Load Power Consumption Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 12V 1.25A 1.25A Power (Watts) 15W No Load Power Consumption 500mW (Max) Positive Center 4.20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 1.25A 1.25A 1.25A 1.25A 1.25A 1.25C Output Consumption 1.25A 1.25C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) No Load Power Consumption 500mW (Max) Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 15W No Load Power Consumption 500mW (Max) Positive Center Level V Commercial) Level V -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm	Voltage - Output	12V
No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5 \text{mm}$ O.D. $x 11.0 \text{mm}$ Size / Dimension 3.58 " L $x 1.50$ " W $x 1.42$ " H (91.0mm $x 38.0 \text{mm}$ $x 36.0 \text{mm}$)	Current - Output (Max)	1.25A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Power (Watts)	15W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $3.58^{\circ}\text{L} \times 1.50^{\circ}\text{W} \times 1.42^{\circ}\text{H} (91.0\text{mm} \times 38.0\text{mm} \times 36.0\text{mm})$	Polarization	Positive Center
Operating Temperature -20°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Efficiency	Level V
Size / Dimension 3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)	Operating Temperature	-20°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm
Report errors?	Size / Dimension	3.58" L x 1.50" W x 1.42" H (91.0mm x 38.0mm x 36.0mm)
		Report errors?

AEL15US12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AEL15US12 Payment Methods





















AEL15US12 Shipping Methods













If you have any question about AEL15US12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com