

AEU65-480 Information



For Reference Only

Part Number AEU65-480
Manufacturer Triad Magnetics

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 65W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A TOTAL # 400	G
AEU65-480	Specifications

Manufacturer Part Number AEU65-480 Manufacturer Triad Magnetics Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series AEU65 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	<u>•</u>	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series AEU65 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Manufacturer Part Number	AEU65-480
Package - Series AEU65 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Manufacturer	Triad Magnetics
Package - Series AEU65 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series AEU65 Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Strice - Isolation 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension Enclosed 10 10 10 10 10 10 10 10 10 1	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 1.35A Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Series	AEU65
Voltage - Input Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Туре	Enclosed
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Site / Operating Temperature Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Courrent - Output 4 - Current - Output (Max) - Size / Dimension - Current - Output 4 - Current - Output (Max) - Adjustable Output, DC Input Capable, Universal Input Chassis Mount Size / Dimension - Chassis Mount 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sity (3000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension - Output A (110.0mm x 78.0mm x 35.0mm)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 65W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Current - Output (Max)	1.35A
Voltage - Isolation 3kV (3000V) Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Power (Watts)	65W
Efficiency 81% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Voltage - Isolation	3kV (3000V)
Features Adjustable Output, DC Input Capable, Universal Input Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Efficiency	81%
Mounting Type Chassis Mount Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)	Features	Adjustable Output, DC Input Capable, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.33" L x 3.07" W x 1.38" H (110.0mm x 78.0mm x 35.0mm)
		Report errors?

AEU65-480 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AEU65-480 Payment Methods



















AEU65-480 Shipping Methods













If you have any question about AEU65-480, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com