



#### AF122-FR-0756KL Information

Heisener.com

Part Number AF122-FR-0756KL

**Manufacturer** Yageo **Category** Resistors

Resistor Networks, Arrays

**Description** RES ARRAY 2 RES 56K OHM 0404

Package 0404 (1010 Metric), Convex

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# AF122-FR-0756KL Specifications

| Manufacturer Part Number         AF122-FR-0756KL           Manufacturer         Yageo           Category         Resistors           Package         0404 (1010 Metric), Convex           Series         AF122           Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)  |                          |                                       |
|--|--------------------------|---------------------------------------|
| Category         Resistors           Resistor Networks, Arrays           Package         0404 (1010 Metric), Convex           Series         AF122           Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)  | Manufacturer Part Number | AF122-FR-0756KL                       |
| Resistor Networks, Arrays           Package         0404 (1010 Metric), Convex           Series         AF122           Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)   | Manufacturer             | Yageo                                 |
| Package         0404 (1010 Metric), Convex           Series         AF122           Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)   | Category                 | Resistors                             |
| Series         AF122           Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)  |                          | Resistor Networks, Arrays             |
| Circuit Type         Isolated           Resistance (Ohms)         56k           Tolerance         ±1%           Number of Resistors         2           Number of Pins         4           Power Per Element         62.5mW           Temperature Coefficient         ±200ppm/°C           Operating Temperature         -55°C ~ 155°C           Applications         DDRAM, SDRAM           Mounting Type         Surface Mount           Package / Case         0404 (1010 Metric), Convex           Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)   | Package                  | 0404 (1010 Metric), Convex            |
| Resistance (Ohms)  Tolerance  ±1%  Number of Resistors  2  Number of Pins  4  Power Per Element  62.5mW  Temperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 155°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Convex  Supplier Device Package  0404  Size / Dimension  Height - Seated (Max)  56k  ±1%  DURAM, SDRAM  62.5mW  62.5mV  62.5 | Series                   | AF122                                 |
| Tolerance ±1%  Number of Resistors 2  Number of Pins 4  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 155°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Convex  Supplier Device Package 0404  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)  | Circuit Type             | Isolated                              |
| Number of Resistors  2 Number of Pins  4 Power Per Element  62.5mW  Temperature Coefficient  200ppm/°C  Operating Temperature  -55°C ~ 155°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Convex  Supplier Device Package  0404  Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)   | Resistance (Ohms)        | 56k                                   |
| Number of Pins 4  Power Per Element 62.5mW  Temperature Coefficient ±200ppm/°C  Operating Temperature -55°C ~ 155°C  Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Convex  Supplier Device Package 0404  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)  | Tolerance                | ±1%                                   |
| Power Per Element  Emperature Coefficient  ±200ppm/°C  Operating Temperature  -55°C ~ 155°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Convex  Supplier Device Package  0404  Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)  | Number of Resistors      | 2                                     |
| Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Convex  Supplier Device Package 0404  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)  | Number of Pins           | 4                                     |
| Operating Temperature  -55°C ~ 155°C  Applications  DDRAM, SDRAM  Mounting Type  Surface Mount  Package / Case  0404 (1010 Metric), Convex  Supplier Device Package  0404  Size / Dimension  0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max)  0.016" (0.40mm)   | Power Per Element        | 62.5mW                                |
| Applications DDRAM, SDRAM  Mounting Type Surface Mount  Package / Case 0404 (1010 Metric), Convex  Supplier Device Package 0404  Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm)  Height - Seated (Max) 0.016" (0.40mm)   | Temperature Coefficient  | ±200ppm/°C                            |
| Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)  | Operating Temperature    | -55°C ~ 155°C                         |
| Package / Case       0404 (1010 Metric), Convex         Supplier Device Package       0404         Size / Dimension       0.039" L x 0.039" W (1.00mm x 1.00mm)         Height - Seated (Max)       0.016" (0.40mm)  | Applications             | DDRAM, SDRAM                          |
| Supplier Device Package         0404           Size / Dimension         0.039" L x 0.039" W (1.00mm x 1.00mm)           Height - Seated (Max)         0.016" (0.40mm)  | Mounting Type            | Surface Mount                         |
| Size / Dimension       0.039" L x 0.039" W (1.00mm x 1.00mm)         Height - Seated (Max)       0.016" (0.40mm)   | Package / Case           | 0404 (1010 Metric), Convex            |
| Height - Seated (Max) 0.016" (0.40mm)  | Supplier Device Package  | 0404                                  |
|  | Size / Dimension         | 0.039" L x 0.039" W (1.00mm x 1.00mm) |
| Report errors?   | Height - Seated (Max)    | 0.016" (0.40mm)                       |
|  |                          | Report errors?                        |

#### AF122-FR-0756KL Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **AF122-FR-0756KL Payment Methods**





















### AF122-FR-0756KL Shipping Methods













If you have any question about AF122-FR-0756KL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com