



AF122-FR-077K5L Information

Heisener.com

Part Number AF122-FR-077K5L

Manufacturer Yageo **Category** Resistors

Resistor Networks, Arrays

Description RES ARRAY 2 RES 7.5K OHM 0404

Package 0404 (1010 Metric), Convex

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AF122-FR-077K5L Specifications

Manufacturer AF122-FR-077K5L Manufacturer Yageo Category Resistors Resistor Networks, Arrays Package 0404 (1010 Metric), Convex Series AF122 Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)		
Category Resistors Resistor Networks, Arrays Package 0404 (1010 Metric), Convex Series AF122 Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Manufacturer Part Number	AF122-FR-077K5L
Resistor Networks, Arrays Package 0404 (1010 Metric), Convex Series AF122 Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Manufacturer	Yageo
Package 0404 (1010 Metric), Convex Series AF122 Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Category	Resistors
Series AF122 Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Package	0404 (1010 Metric), Convex
Resistance (Ohms) 7.5k Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Series	AF122
Tolerance ±1% Number of Resistors 2 Number of Pins 4 Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Circuit Type	Isolated
Number of Resistors2Number of Pins4Power Per Element62.5mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case0404 (1010 Metric), ConvexSupplier Device Package0404Size / Dimension0.039" L x 0.039" W (1.00mm x 1.00mm)Height - Seated (Max)0.016" (0.40mm)	Resistance (Ohms)	7.5k
Number of Pins Power Per Element 62.5mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Tolerance	±1%
Power Per Element 62.5mW Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Number of Resistors	2
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Number of Pins	4
Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Power Per Element	62.5mW
Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Operating Temperature	-55°C ~ 155°C
Package / Case 0404 (1010 Metric), Convex Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Applications	DDRAM, SDRAM
Supplier Device Package 0404 Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Mounting Type	Surface Mount
Size / Dimension 0.039" L x 0.039" W (1.00mm x 1.00mm) Height - Seated (Max) 0.016" (0.40mm)	Package / Case	0404 (1010 Metric), Convex
Height - Seated (Max) 0.016" (0.40mm)	Supplier Device Package	0404
	Size / Dimension	0.039" L x 0.039" W (1.00mm x 1.00mm)
Report errors?	Height - Seated (Max)	0.016" (0.40mm)
		Report errors?

AF122-FR-077K5L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AF122-FR-077K5L Payment Methods



















AF122-FR-077K5L Shipping Methods













If you have any question about AF122-FR-077K5L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com