



AF164-FR-0776R8L Information



For Reference Only

Part Number AF164-FR-0776R8L

Manufacturer Yageo **Category** Resistors

Resistor Networks, Arrays

Description RES ARRAY 4 RES 76.8 OHM 1206

Package 1206 (3216 Metric), Convex, Long Side Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AF164-FR-0776R8L Specifications

Manufacturer Part NumberAF164-FR-0776R8LManufacturerYageoCategoryResistorsResistor Networks, ArraysPackage1206 (3216 Metric), Convex, Long Side TerminalsSeriesAF164Circuit TypeIsolatedResistance (Ohms)76.8Tolerance±1%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±250ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Convex, Long Side TerminalsSupplier Device Package1206		
Resistors Resistor Networks, Arrays Package 1206 (3216 Metric), Convex, Long Side Terminals Series AF164 Circuit Type Isolated Resistance (Ohms) 76.8 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Manufacturer Part Number	AF164-FR-0776R8L
Resistor Networks, ArraysPackage1206 (3216 Metric), Convex, Long Side TerminalsSeriesAF164Circuit TypeIsolatedResistance (Ohms)76.8Tolerance±1%Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±250ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Convex, Long Side Terminals	Manufacturer	Yageo
Package 1206 (3216 Metric), Convex, Long Side Terminals Series AF164 Circuit Type Isolated Resistance (Ohms) 76.8 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Category	Resistors
Series AF164 Circuit Type Isolated Resistance (Ohms) 76.8 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 76.8 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Package	1206 (3216 Metric), Convex, Long Side Terminals
Resistance (Ohms) 76.8 Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Series	AF164
Tolerance ±1% Number of Resistors 4 Number of Pins 8 Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Circuit Type	Isolated
Number of Resistors4Number of Pins8Power Per Element62.5mWTemperature Coefficient±250ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Convex, Long Side Terminals	Resistance (Ohms)	76.8
Number of Pins8Power Per Element62.5mWTemperature Coefficient±250ppm/°COperating Temperature-55°C ~ 155°CApplicationsDDRAM, SDRAMMounting TypeSurface MountPackage / Case1206 (3216 Metric), Convex, Long Side Terminals	Tolerance	$\pm 1\%$
Power Per Element 62.5mW Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Number of Resistors	4
Temperature Coefficient ±250ppm/°C Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Number of Pins	8
Operating Temperature -55°C ~ 155°C Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Power Per Element	62.5mW
Applications DDRAM, SDRAM Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Temperature Coefficient	±250ppm/°C
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Operating Temperature	-55°C ~ 155°C
Package / Case 1206 (3216 Metric), Convex, Long Side Terminals	Applications	DDRAM, SDRAM
	Mounting Type	Surface Mount
Supplier Device Package 1206	Package / Case	1206 (3216 Metric), Convex, Long Side Terminals
	Supplier Device Package	1206
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Height - Seated (Max) 0.028" (0.70mm)	Height - Seated (Max)	0.028" (0.70mm)
Report errors?		Report errors?

AF164-FR-0776R8L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AF164-FR-0776R8L Payment Methods

































If you have any question about AF164-FR-0776R8L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com