

## **AFD50-12-8SY Information**

Heisener.com

Part Number AFD50-12-8SY

Manufacturer TE Connectivity Deutsch Connectors

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 8POS FLANGE W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **AFD50-12-8SY Specifications**

| Manufacturer Part Number       AFD50-12-8SY         Manufacturer       TE Connectivity Deutsch Connectors         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 G Series II, AFD         Connector Type       Receptacle, Female Sockets         Number of Positions       8         Shell Size - Insert       12-8         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       Y         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated         Contact Finish       Gold         Features       -         Voltage - Rated       -         Current Rating       7.5A |                          |                                    |
|--|--------------------------|------------------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A  | Manufacturer Part Number | AFD50-12-8SY                       |
| Package-SeriesMIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   | Manufacturer             | TE Connectivity Deutsch Connectors |
| Package-SeriesMIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   | Category                 | Connectors, Interconnects          |
| SeriesMIL-DTL-26482 G Series II, AFDConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   |                          | Circular Connectors                |
| Connector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   | Package                  | -                                  |
| Number of Positions8Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   | Series                   | MIL-DTL-26482 G Series II, AFD     |
| Shell Size - Insert12-8Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A   | Connector Type           | Receptacle, Female Sockets         |
| Shell Size, MIL  Mounting Type Panel Mount, Flange  Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated  Contact Finish Features Odd Features Voltage - Rated Current Rating 7.5A  | Number of Positions      | 8                                  |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationYIngress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated-Current Rating7.5A  | Shell Size - Insert      | 12-8                               |
| Termination Crimp Fastening Type Bayonet Lock Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7,5A   | Shell Size, MIL          | -                                  |
| Fastening Type  Orientation  Y  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  Asyonet Lock  Bayonet Lock  Aluminum  Aluminum, Nickel Plated  Gold  -  7.5A   | Mounting Type            | Panel Mount, Flange                |
| Orientation Y Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A   | Termination              | Crimp                              |
| Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A   | Fastening Type           | Bayonet Lock                       |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Nickel Plated   | Orientation              | Y                                  |
| Contact Finish Gold Features - Voltage - Rated - Current Rating 7.5A   | Ingress Protection       | Environment Resistant              |
| Features - Voltage - Rated - Current Rating 7.5A   | Shell Material, Finish   | Aluminum, Nickel Plated            |
| Voltage - Rated - Current Rating 7.5A  | Contact Finish           | Gold                               |
| Current Rating 7.5A  | Features                 | -                                  |
|  | Voltage - Rated          | -                                  |
| Report errors?   | Current Rating           | 7.5A                               |
|  |                          | Report errors?                     |

#### **AFD50-12-8SY Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **AFD50-12-8SY Payment Methods**



















### **AFD50-12-8SY Shipping Methods**













If you have any question about AFD50-12-8SY, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com