

AFK686M2AH32B-F

AFK686M2AH32B-F Information



Part Number	AFK686M2AH32B-F
Manufacturer	Cornell Dubilier Electronics (CDE)
Category	Capacitors Aluminum Electrolytic Capacitors
Description	CAP ALUM 68UF 20% 100V SMD
Package	Radial, Can - SMD
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AFK686M2AH32B-F Specifications

Manufacturer Part NumberAFK 686 M2A H32B-FManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageAluninum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAFKCapacitance68 µFTolerance100 VVoltage - Rated100 VESR (Equivalent Series Resistance)300 mOhn @ 100 kHzOperating Temperature5000 Hrs @ 105 °COperating Temperature66 µFApplicationsGeneral PurposeApplicationsGonda @ 100 kHzApple Current - High Frequency300 mAn @ 100 kHzImpedance300 mAn @ 100 kHzApple Current - High Frequency300 mAn @ 100 kHzAngel Current - Marcine Series300 mAn @ 100 kHzApple Current - High Frequency300 mAn @ 100 kHzApple Current - Marcine Series300 mAn @ 100 kHzApple Current - High Frequency300 mAn @ 100 kHz
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAFKCapacitance68µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzStom A @ 100kHz500mA @ 100kHz
APackageRadial, Can - SMDSeriesAFKCapacitance68μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency300mA @ 100kHzSoon A @ 100kHzSoon A @ 100kHz
PackageRadial, Can - SMDSeriesAFKCapacitance68μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency500mA @ 100kHz
SeriesAFKCapacitance68µFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 100kHzRipple Current - High Frequency500mA @ 100kHz
Capacitance68μFTolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Tolerance±20%Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Voltage - Rated100VESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
ESR (Equivalent Series Resistance)320 mOhm @ 100kHzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
ApplicationsGeneral PurposeRipple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Ripple Current - Low Frequency375mA @ 120HzRipple Current - High Frequency500mA @ 100kHz
Ripple Current - High Frequency500mA @ 100kHz
Impedance 320 mOhms
Lead Spacing -
Size / Dimension 0.492" Dia (12.50mm)
Height - Seated (Max) 0.551" (14.00mm)
Surface Mount Land Size 0.531" L x 0.590" W (13.50mm x 15.00mm)
Mounting Type Surface Mount
Package / Case Radial, Can - SMD
Report errors

AFK686M2AH32B-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AFK686M2AH32B-F Payment Methods



If you have any question about AFK686M2AH32B-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com