

### AGC-V-1/16-R Information



For Reference Only

Part Number AGC-V-1/16-R

Manufacturer Eaton

Category Circuit Protection

**Fuses** 

**Description** FUSE GLASS 63MA 250VAC 3AB 3AG

**Package** 3AB, 3AG, 1/4" x 1-1/4" (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **AGC-V-1/16-R Specifications**

Manufacturer Part NumberAGC-V-1/16-RManufacturerEatonCategoryCircuit ProtectionPackage3AB, 3AG, 1/4" x 1-1/4" (Axial)SeriesAGCFuse TypeCartridge, GlassCurrent Rating63mAVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastPackage / Case3AB, 3AG, 1/4" x 1-1/4" (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage35AMelting 12t0.000181ApprovalsCSA, ULOperating Temperature-Color-Size / Dimension0.266" Dia x 1.292" L (6.76mm x 32.82mm)Report errors?	•	
Category         Circuit Protection           Fuses           Package         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Series         AGC           Fuse Type         Cartridge, Glass           Current Rating         63mA           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Package / Case         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         35A           Melting 12t         0.000181           Approvals         CSA, UL           Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Manufacturer Part Number	AGC-V-1/16-R
Fuses           Package         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Series         AGC           Fuse Type         Cartridge, Glass           Current Rating         63mA           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Package / Case         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         35A           Melting I2t         0.000181           Approvals         CSA, UL           Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Manufacturer	Eaton
Package       3AB, 3AG, 1/4" x 1-1/4" (Axial)         Series       AGC         Fuse Type       Cartridge, Glass         Current Rating       63mA         Voltage Rating - AC       250V         Voltage Rating - DC       -         Response Time       Fast         Package / Case       3AB, 3AG, 1/4" x 1-1/4" (Axial)         Mounting Type       Through Hole         Breaking Capacity @ Rated Voltage       35A         Melting I2t       0.000181         Approvals       CSA, UL         Operating Temperature       -         Color       -         Size / Dimension       0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Category	Circuit Protection
Series         AGC           Fuse Type         Cartridge, Glass           Current Rating         63mA           Voltage Rating - AC         250V           Voltage Rating - DC         -           Response Time         Fast           Package / Case         3AB, 3AG, 1/4" x 1-1/4" (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         35A           Melting I2t         0.000181           Approvals         CSA, UL           Operating Temperature         -           Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)		Fuses
Fuse Type Current Rating 63mA Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature Color Size / Dimension Cartridge, Glass Cama Cama Cama Cama Cama Cama Cana Catridge, Glass Cama Cama Cama Cama Cama Cama Catridge, Glass Cama Cama Cama Cama Colov  - Catridge, Glass Cama Cama Cama Catridge, Glass Cama Cama Catridge, Catridge Catridge, Ca	Package	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 0.000181  Approvals CSA, UL Operating Temperature Color Size / Dimension  63mA 250W  150m 150m 150m 150m 150m 150m 150m 150	Series	AGC
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CSA, UL  Operating Temperature  Color  Size / Dimension  250V	Fuse Type	Cartridge, Glass
Voltage Rating - DC  Response Time Fast  Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 35A  Melting I2t 0.000181  Approvals CSA, UL  Operating Temperature - Color - Size / Dimension  -  0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Current Rating	63mA
Response Time Fast Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole Breaking Capacity @ Rated Voltage 35A  Melting I2t 0.000181  Approvals CSA, UL  Operating Temperature - Color - Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Voltage Rating - AC	250V
Package / Case 3AB, 3AG, 1/4" x 1-1/4" (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 35A  Melting I2t 0.000181  Approvals CSA, UL  Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CSA, UL  Operating Temperature  Color  Size / Dimension  Through Hole  35A  0.000181  CSA, UL  0.000181  - (CSA, UL)  - (COLOT)  - (COLOT)  0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Response Time	Fast
Breaking Capacity @ Rated Voltage 35A  Melting I2t 0.000181  Approvals CSA, UL  Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Package / Case	3AB, 3AG, 1/4" x 1-1/4" (Axial)
Melting I2t       0.000181         Approvals       CSA, UL         Operating Temperature       -         Color       -         Size / Dimension       0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Mounting Type	Through Hole
Approvals CSA, UL  Operating Temperature - Color - Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Breaking Capacity @ Rated Voltage	35A
Operating Temperature -  Color -  Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Melting I2t	0.000181
Color         -           Size / Dimension         0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Approvals	CSA, UL
Size / Dimension 0.266" Dia x 1.292" L (6.76mm x 32.82mm)	Operating Temperature	-
	Color	-
Report errors?	Size / Dimension	0.266" Dia x 1.292" L (6.76mm x 32.82mm)
		Report errors?

### AGC-V-1/16-R Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# AGC-V-1/16-R Payment Methods





















# AGC-V-1/16-R Shipping Methods













If you have any question about AGC-V-1/16-R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com