



AGN20003 Information



For Reference Only

Part Number AGN20003

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGN20003 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Relays Signal Relays, Up to 2 Amps Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ams Release Time AGN Relays Signal Relays, Up to 2 Amps Signal Relays, Up to 2 Amps AGN Panasonic Electric Works Relays Panasonic Electric Works Panasonic Electric Works Panasonic Electric Works Relays Panasonic Electric Works Signal Relays Lectron Lectron Signal Relays Lectron Signal Relays Lectron Signal Relays Lectron Signal Relays Lectron Lectron Lectron Lectron Lectron Lectron Lectron Lectron Lec		
Category Relays Signal Relays, Up to 2 Amps Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms	Manufacturer Part Number	AGN20003
Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Operate Time 4ms	Manufacturer	Panasonic Electric Works
Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Category	Relays
Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Package	-
Coil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4ms	Series	AGN
Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Relay Type	Telecom
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Coil Voltage	3VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 0.3 VDC 4ms	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms	Turn On Voltage (Max)	2.25 VDC
	Turn Off Voltage (Min)	0.3 VDC
Release Time 4ms	Operate Time	4ms
	Release Time	4ms
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

AGN20003 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGN20003 Payment Methods





















AGN20003 Shipping Methods













If you have any question about AGN20003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com