

AGN20012 Information



For Reference Only

Part Number AGN20012

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGN20012 Specifications

Manufacturer Part Number AGN20012 Manufacturer Panasonic Electric Works Category Relays Signal Relays, Up to 2 Amps Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 11.7mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current11.7mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	AGN20012
Package-SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current11.7mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series AGN Relay Type Telecom Coil Type Non Latching Coil Current 11.7mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current11.7mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current11.7mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current11.7mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	AGN
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style 11.7mA 11.7mA 11.7mA 12.VDC 4ms Tann Cf) Turn Cf) Turn Cf) Turn Off Voltage (Min) Through Hole Termination Style	Relay Type	Telecom
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Coil Current	11.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style 9 VDC 4ms - 4ms 4ms PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style 1.2 VDC 4ms Through Hole PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

AGN20012 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGN20012 Payment Methods



















AGN20012 Shipping Methods













If you have any question about AGN20012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com