



AGN210A4H Information



For Reference Only

Part Number AGN210A4H

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGN210A4H Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series AGN Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Description Category Relays Signal Relays Latching (Part of 2 Amps Latching, Single Coil Latc		
CategoryRelaysPackage-SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	AGN210A4H
Package-SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package-SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	AGN
Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 1A 4ms 125VAC, 110VDC - Max 4.10VDC - Max 4.10VDC - Max 5.10VDC - Max 6.10VDC - Max 6.10	Coil Current	22.2mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	4.5VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style 3.38 VDC - 4ms 5uns 4ms 6uns	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	3.38 VDC
Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	4ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	4ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
D (0	Termination Style	Gull Wing
Report errors?		Report errors?

AGN210A4H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGN210A4H Payment Methods



















AGN210A4H Shipping Methods













If you have any question about AGN210A4H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com