



AGN210S09 Information



For Reference Only

Part Number AGN210S09

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 9V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGN210S09 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series AGN Relay Type Telecom Coil Type Latching, Single Coil Coil Current 11.1mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Panet aware? Panet aware?		
CategoryRelaysPackage-SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	AGN210S09
Package-SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package - Series AGN Relay Type Telecom Coil Type Latching, Single Coil Coil Current 11.1mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Goil	Category	Relays
SeriesAGNRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeLatching, Single CoilCoil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	AGN
Coil Current11.1mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Relay Type	Telecom
Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 1A 4ms 6.75 VDC - Mounting Type Surface Mount Gull Wing	Coil Current	11.1mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style	Coil Voltage	9VDC
Switching Voltage Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style 6.75 VDC - 4ms 5uns 6.75 VDC - 6.7	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	6.75 VDC
Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	4ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	4ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Donost owors?	Termination Style	Gull Wing
Report errors?		Report errors?

AGN210S09 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGN210S09 Payment Methods





















AGN210S09 Shipping Methods













If you have any question about AGN210S09, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com