

#### **AGN260S24 Information**



For Reference Only

Part Number AGN260S24

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **AGN260S24 Specifications**

| Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package   |                          |                             |
|--|--------------------------|-----------------------------|
| CategoryRelaysPackage-SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing | Manufacturer Part Number | AGN260S24                   |
| Package-SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing               | Manufacturer             | Panasonic Electric Works    |
| Package-SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing               | Category                 | Relays                      |
| SeriesAGNRelay TypeTelecomCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing                       |                          | Signal Relays, Up to 2 Amps |
| Relay TypeTelecomCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing                                | Package                  | -                           |
| Coil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing   | Series                   | AGN                         |
| Coil Current 5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Mounting Type Surface Mount Termination Style Gull Wing   | Relay Type               | Telecom                     |
| Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features  | Coil Type                | Non Latching                |
| Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Surface Mount  Termination Style  DPDT (2 Form C)  1A  1A  19.2 VDC - Max  19.2 VDC  2.4 VDC  4ms  Gull Wing    | Coil Current             | 5mA                         |
| Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Surface Mount  Termination Style  | Coil Voltage             | 24VDC                       |
| Switching Voltage  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Surface Mount  Termination Style  125VAC, 110VDC - Max  19.2 VDC  4ms  5uface Mount  Gull Wing   | Contact Form             | DPDT (2 Form C)             |
| Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  4ms  Release Time  4ms  Features  - Mounting Type  Surface Mount  Termination Style  19.2 VDC  2.4 VDC  4ms  4ms  Gull Wing  | Contact Rating (Current) | 1A                          |
| Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing  | Switching Voltage        | 125VAC, 110VDC - Max        |
| Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing   | Turn On Voltage (Max)    | 19.2 VDC                    |
| Release Time 4ms  Features - Mounting Type Surface Mount Termination Style Gull Wing   | Turn Off Voltage (Min)   | 2.4 VDC                     |
| Features - Mounting Type Surface Mount Termination Style Gull Wing   | Operate Time             | 4ms                         |
| Mounting Type Surface Mount Termination Style Gull Wing  | Release Time             | 4ms                         |
| Termination Style Gull Wing  | Features                 | -                           |
|  | Mounting Type            | Surface Mount               |
| Report errors?   | Termination Style        | Gull Wing                   |
|  |                          | Report errors?              |

#### **AGN260S24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **AGN260S24 Payment Methods**



















## **AGN260S24 Shipping Methods**













If you have any question about AGN260S24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com