

AGQ200S03 Information



For Reference Only

Part Number AGQ200S03

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ200S03 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package		
CategoryRelaysPackage-SeriesAGQRelay TypeTelecomCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	AGQ200S03
Package-SeriesAGQRelay TypeTelecomCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package - Series AGQ Relay Type Telecom Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gella Comment of the surface Mount of the surface Mount Termination Style Gella Comment of the surface Mount of the surfa	Category	Relays
SeriesAGQRelay TypeTelecomCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	AGQ
Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 2A 125VAC, 110VDC - Max 4.10VDC - Max 4.10VDC - Max 4.10VDC - Max 5.10VDC 6.10VDC 6.1	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	3VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style 125VAC, 110VDC - Max 2.25 VDC 0.3 VDC 4ms 4ms 5urface Mount Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ams Release Time 4ms Features - Mounting Type Surface Mount Termination Style 2.25 VDC 4ms 4ms 5und 4ms 6und 6u	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style O.3 VDC 4ms 5urface Mount Gull Wing	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	2.25 VDC
Release Time 4ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	4ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	4ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

AGQ200S03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ200S03 Payment Methods



















AGQ200S03 Shipping Methods













If you have any question about AGQ200S03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com